Highlights

Bayesian analysis of hierarchical random fields for material modeling

Sebastian Geyer, Iason Papaioannou, Daniel Straub

- We present analytical expressions for the Bayesian analysis of hierarchical Gaussian random fields.
- Closed-form expressions are derived for the posterior distribution of the random field parameters and the posterior predictive Student's *t*-random field.
- The autocorrelation structure is approximated by its maximum a-posteriori estimate and application to non-Gaussian random fields is discussed.
- The connection of the presented methodology to the Bayesian approach in EN 1990 for determining characteristic values is illustrated.
- The application of the approach is demonstrated with data from concrete and geomaterials.

Bayesian analysis of hierarchical random fields for material modeling

Sebastian Geyer^{a,*}, Iason Papaioannou^a, Daniel Straub^a

^aEngineering Risk Analysis Group, Technische Universität München, Arcisstraße 21, 80333 München, Germany

Abstract

In probabilistic assessments, spatially variable material properties are modeled with random fields. These random fields can be learned from spatial data by means of Bayesian analysis. This paper presents analytical expressions for the Bayesian analysis of hierarchical Gaussian random fields. We model the prior spatial distribution by a Gaussian random field with normal-gamma distributed mean and precision and make use of the conjugacy of prior distribution and likelihood function to find the posterior distribution of the random field parameters. We present closed-form expressions for the spatial mean and precision function of the posterior predictive Student's *t*-random field. Furthermore, we discuss the application of the hierarchical model to non-Gaussian random fields (translation random fields) and show the connection of the methodology to the Bayesian approach of EN 1990 for estimating characteristic values for material parameters. The method is illustrated on two spatial data sets of concrete and soil strength parameters.

Keywords: Gaussian random fields, Student's *t*-distribution, analytical update, Bayesian analysis, spatial variability, conjugate prior

Preprint submitted to Probabilistic Engineering Mechanics

^{*}Corresponding author

Email address: s.geyer@tum.de (Sebastian Geyer)

1 1. Introduction

Setting up an engineering model requires definition of material properties. To correctly account for their inherent randomness, such material properties are commonly modeled probabilistically. A probabilistic representation with random variables is sufficient for modeling materials without or with negligible spatial variability. However, in many applications the effects of the spatial variability of materials should not be neglected in the modeling process. This is the case, e.g., with soil parameters in geotechnical assessments [1], and material parameters in assessments of large concrete structures [e.g. 2].

Spatially variable uncertain quantities can be modeled by random fields 10 (RFs). An RF represents a random variable at each point of a spatial domain [3]. 11 A complete definition of the RF requires specification of the joint distribution 12 of the variables corresponding to any collection of points of the spatial domain. 13 This is nontrivial in general with the exception of Gaussian and a special case 14 of non-Gaussian RFs, termed translation RFs. Translation RFs are RFs that 15 can be expressed as functions of Gaussian RFs [4], e.g., a lognormal RF can be 16 expressed as the exponential of a Gaussian RF. A Gaussian RF implies that the 17 joint distribution for any collection of points is multivariate Gaussian and can 18 be completely defined by the first- and second-moment functions [5]. Gaussian 19 RFs have well established statistical properties and a variety of methods are 20 available for simulating them [e.g. 6]. 21

RFs can be learned from data through Bayesian analysis [7]. In the general case, such an update needs to be done numerically with methods usually
based on Monte Carlo sampling, including Markov chain Monte Carlo methods
[8], sequential Monte Carlo methods [9, 10] and subset simulation [11, 12, 13].
However, Gaussian RFs enable the use of conjugate priors to learn the RF
parameters via a closed-form update in a Bayesian analysis [14, 2].

RFs have been used for a long time in the field of geostatistics for the interpolation of spatial data by means of kriging, which includes Bayesian inference
of Gaussian RF parameters [e.g. 15, 16]. A comprehensive review of hierarchi-

cal Bayesian analysis with spatial data from the viewpoint of geostatistics can 31 be found in [17]. More recently, these approaches have gained importance in 32 the field of machine learning. They are used for Gaussian process regression, 33 which is a versatile surrogate model for random functions with noisy observa-34 tions [18]. In the engineering community, the potential of accounting for spatial 35 variability within Bayesian analysis has been recognized especially in the field 36 of geotechnical engineering [e.g. 19, 20, 21, 22]. Therein, it is often essential to 37 identify site-specific trend functions of soil properties in addition to the inherent 38 spatial variability. Recently, attempts have been made to simultaneously learn 39 the trend function and autocovariance function with sparse measurements in a 40 Bayesian analysis. The approach of [23, 24, 25] applies sparse Bayesian learning 41 to learn the trend function of the RF and subsequently draws samples from the 42 posterior distribution of the RF parameters through Markov chain Monte Carlo 43 methods. The authors of 26 applied Bayesian compressive sampling to repre-44 sent non-homogeneous RFs. This approach does not require the explicit choice 45 of a prior RF model. It expresses the RF as a superposition of a set of basis 46 functions and evaluates the posterior distribution of the coefficients of these 47 functions using sparse measurements. The method has been combined with the 48 Karhunen-Loève expansion to obtain realizations of the RF [27, 28, 29], and 49 has been recently extended to treat multi-dimensional and cross-correlated RFs 50 [30, 31].51

Bayesian approaches have also found their way into other engineering fields,
e.g., for estimating design values of structural material properties when samples
are available [32, 33], which is also included in the current European standards
for constructions (EN 1990) [34].

The aim of this paper is to present a hierarchical Bayesian model for material properties modeled with Gaussian or translation RFs. Hierarchical Gaussian Bayesian models have been well developed in the context of Bayesian linear regression [e.g. 7] and hierarchical spatial modeling [e.g. 35]. This work applies existing results from these fields to derive a comprehensive hierarchical RF model that can be used in the context of stochastic material modeling. We make

use of the fact that the normal-gamma distribution is the conjugate prior for 62 the mean and precision of a Gaussian RF to obtain the posterior distribution of 63 the RF parameters. The posterior predictive RF is a non-homogeneous RF with 64 Student's t-marginal distribution. Importantly, given a prior distribution for the 65 RF parameters and a chosen autocorrelation function, all steps of the Bayesian 66 analysis can be performed in closed form, providing marginal and multivariate 67 solutions for the posterior predictive RF model. This property should simplify 68 application in practice, especially in engineering domains where accounting for 69 spatial variability is currently not common practice. Moreover, we discuss how 70 existing approaches for simulation of Gaussian RFs can be applied to gener-71 ate realizations of the derived RF model. The application to situations with 72 non-Gaussian translation prior RFs is investigated and for the specific case of 73 lognormal prior distribution, the equations for the required transformation are 74 given. Furthermore, we discuss the influence of the prior correlation function 75 and a posterior point estimate of its parameters. Finally, we show that the 76 presented updating approach is a generalization of the Bayesian approach for 77 evaluation of characteristic values of EN 1990. 78

The structure of the paper is as follows. Section 2 presents the structure 79 of the hierarchical RF, followed by a short review of Bayesian analysis and a 80 step-by-step presentation of the proposed Bayesian updating procedure. Sec-81 tion 3 applies the method to two examples from different engineering fields 82 (geotechnical engineering and structural engineering). A summary and main 83 conclusions are given in Section 4. The analytical expressions for updating the 84 RF are derived in Appendices A to C and Appendix D describes properties of 85 the log-Student's *t*-distribution. 86

87 2. Methodology

In a Gaussian RF X(z), the joint distribution of $\{X(z_i), i = 1, ..., n\}$ for any $z_i \in \Omega \subset \mathbb{R}^d$ and $n \in \mathbb{N}$ is jointly Gaussian, with Ω denoting the domain of definition of the RF and d the spatial dimension of Ω [5]. This RF is fully

described by the spatial functions for the mean value, the variance and the 91 autocorrelation. Closed-form solutions are available for the posterior distribu-92 tion of the RF given data **M** of X [7, 36]. We consider a prior RF for X(z)93 with homogeneous point statistics, i.e., a-priori the RF has constant mean and 94 variance. The vector of uncertain hyperparameters is $\boldsymbol{\theta} = \left[\mu_X, \lambda_X\right]^{\mathsf{T}}$, where 95 μ_X is the mean value and λ_X is the precision (inverse of the variance). The 96 assumption of prior homogeneity is a simplification and limits the application 97 to cases without a spatial trend of the RF or cases where a homogeneous RF 98 X(z) can be obtained from the actual RF by a normalization operation [e.g., 3] 99 or by de-trending methods [e.g., 37, 38]. Figure 1 summarizes the investigated



Figure 1: The hierarchical RF model to learn X(z) from **M**. μ_X and λ_X are the mean and precision of the RF X(z) and **M** is the measurement data. τ is the vector of parameters of the autocorrelation function.

100

problem setting, where the nodes represent uncertain quantities (the random 101 variables and the RF) and the arrows denote the direct dependencies among 102 them [e.g. 39]. τ is the vector of correlation parameters, i.e., the parameters of 103 the autocorrelation function of the RF. These are initially considered as deter-104 ministic; the estimation of τ from the data M is discussed in Section 2.7. It is 105 worth noting that the method can handle arbitrary autocorrelation functions, 106 i.e., we do not require the autocorrelation function to depend on the difference 107 in location, although in most applications this is a standard choice. The aim 108 of the analysis is to learn X(z) conditional on **M**. The individual steps of the 109

analysis are derived in the following, preceded by a short introduction to thebasics of Bayesian analysis.

112 2.1. Bayesian analysis

¹¹³ When performing a Bayesian analysis, the first step is setting up a prior joint ¹¹⁴ probability density function (PDF) of the parameters $\boldsymbol{\theta}$. The prior PDF $f(\boldsymbol{\theta})$ ¹¹⁵ is then updated to the posterior PDF $f(\boldsymbol{\theta}|\mathbf{M})$ with data \mathbf{M} , by application of ¹¹⁶ Bayes' rule [7]:

$$f(\boldsymbol{\theta}|\mathbf{M}) \propto f(\boldsymbol{\theta}) \cdot \mathbf{L}(\boldsymbol{\theta}|\mathbf{M}), \qquad (1)$$

where $L(\boldsymbol{\theta}|\mathbf{M})$ is the likelihood function, summarizing the information from 117 the data **M**. Note that a single data point \mathbf{M}_i may contain various types 118 of information, including the measurement outcome, the measurement loca-119 tion or time, the used measurement device and the environmental conditions 120 at the time of the measurement. In this paper, we focus on the case where 121 **M** contains spatially distributed measurements of an RF X(z). Hence, each 122 \mathbf{M}_i includes the measurement outcome $x_{m,i}$ and the corresponding measure-123 ment location $\boldsymbol{z}_{m,i}$, i.e., $\mathbf{M}_i = [x_{m,i}, \boldsymbol{z}_{m,i}]$. Given a set of *n* direct measure-124 ments of the RF $X(\mathbf{z})$, $\mathbf{M} = [\mathbf{M}_1, \mathbf{M}_2, \dots, \mathbf{M}_n]^{\mathsf{T}}$, with measurement outcomes 125 $\boldsymbol{x}_m = [x_{m,1}, x_{m,2}, \ldots, x_{m,n}]^{\mathsf{T}} \subseteq \mathbb{R}^n$ and corresponding measurement locations 126 $\mathbf{Z}_m = [\mathbf{z}_{m,1}, \ \mathbf{z}_{m,2}, \dots, \ \mathbf{z}_{m,n}]^{\mathsf{T}} \subseteq \mathbb{R}^{n \times d}$, the joint likelihood is the PDF of $X(\mathbf{z})$ 127 at locations \mathbf{Z}_m conditional on $\boldsymbol{\theta}$: 128

$$L(\boldsymbol{\theta}|\mathbf{M}) = f(\boldsymbol{x}_m; \mathbf{Z}_m | \boldsymbol{\theta}).$$
⁽²⁾

129 2.2. Prior model

We consider a Gaussian RF X(z) whose parameter vector $\boldsymbol{\theta}$ has a normalgamma (\mathcal{NG}) prior, with PDF [e.g. 40, 33, 35]

$$f(\boldsymbol{\theta}) = \mathcal{N}\mathcal{G}(\mu_X, \lambda_X | \mu_0, \kappa_0, \alpha_0, \beta_0) = \mathcal{N}(\mu_X | \mu_0, \kappa_0 \lambda_X) \cdot \mathcal{G}(\lambda_X | \alpha_0, \beta_0)$$
$$= \mathcal{C}_0 \lambda_X^{\alpha_0 - \frac{1}{2}} \exp\left(-\lambda_X \left(\frac{\kappa_0}{2} \left(\mu_X - \mu_0\right)^2 + \beta_0\right)\right). \tag{3}$$

 $_{132}$ $\Gamma(\cdot)$ is the gamma function and \mathcal{C}_0 is a normalizing constant, given by

$$C_0 = \frac{\beta_0^{\alpha_0} \kappa_0^{\frac{1}{2}}}{\Gamma(\alpha_0) \left(2\pi\right)^{\frac{1}{2}}}.$$
(4)

The spatial variability of the prior RF is determined by its autocorrelation function $\rho(z_1, z_2)$ [5, 3]. A classical choice for the autocorrelation function is the Matérn model, which includes the exponential model and the squareexponential model [41, 5, 18].

137 2.3. Likelihood function

The likelihood function for learning the RF X(z) with spatially distributed measurements **M** is given by Equation (2). For the Gaussian RF this translates to:

$$L\left(\boldsymbol{\theta}|\mathbf{M}\right) = \frac{\lambda_X^{\frac{n}{2}}}{\left(2\pi\right)^{\frac{n}{2}} \left(\det\left(\mathbf{R}_m\right)\right)^{\frac{1}{2}}} \exp\left(-\frac{\lambda_X}{2} \left(\boldsymbol{x}_m - \mu_X \mathbf{1}_n\right) \mathbf{R}_m^{-1} \left(\boldsymbol{x}_m - \mu_X \mathbf{1}_n\right)^{\mathsf{T}}\right),\tag{5}$$

where \mathbf{R}_m is the correlation matrix of the measurement locations with entry $R_{m,i,j}$ calculated as $\rho(\mathbf{z}_{m,i}, \mathbf{z}_{m,j})$. $\mathbf{1}_n$ denotes a 1 × *n*-vector of ones.

¹⁴³ Uncertainty in the measurement procedure can be accounted for by including ¹⁴⁴ a measurement error ε_i . Assuming an additive measurement error yields the ¹⁴⁵ following relation between the actual value x at location $z_{m,i}$ and the measured ¹⁴⁶ value $x_{m,i}$:

$$x_{m,i} = x\left(\boldsymbol{z}_{m,i}\right) + \varepsilon_i. \tag{6}$$

The error ε_i is often modeled by a zero-mean Gaussian random variable with standard deviation σ_{ε} and statistical independence between the measurement errors at different locations is assumed. In such case, the methodology presented in the following sections is applicable with a minor modification: λ_X does not describe the precision of X(z) but the overall precision of $X(z) + \varepsilon$, i.e.,

$$\lambda_X = \left(\lambda_{X,\text{RF}}^{-1} + \sigma_{\varepsilon}^2\right)^{-1},\tag{7}$$

where $\lambda_{X,\text{RF}}$ is the precision of X(z). Moreover, the autocorrelation function describing the overall variability reads

$$\rho(\boldsymbol{z}_i, \boldsymbol{z}_j) = \rho_{\rm RF}(\boldsymbol{z}_i, \boldsymbol{z}_j) \cdot (1 - \gamma_{\varepsilon}) + \delta(i, j) \cdot \gamma_{\varepsilon}, \qquad (8)$$

where $\rho_{\rm RF}(\boldsymbol{z}_i, \boldsymbol{z}_j)$ denotes the spatial correlation function of $X(\boldsymbol{z})$ and $\gamma_{\varepsilon} = \sigma_{\varepsilon}^2 \lambda_X \in (0, 1)$ is the portion of the overall variance attributed to the measurement error. $\delta(i, j)$ is the Dirac delta function returning 1 if i = j and 0 otherwise.

158 2.4. Posterior distribution of the parameters

In the general case, Equation (1) needs to be solved numerically, e.g. through 159 sampling techniques, due to the intractability of the normalizing constant. How-160 ever, analytical solutions for the posterior distribution are available in some spe-161 cial cases, when using conjugate priors [7, 40]. The chosen \mathcal{NG} prior distribution 162 and the multivariate Gaussian likelihood of Equation (5) are conjugate. Hence, 163 the posterior distribution of θ can be derived analytically and has the same para-164 metric form as the prior, i.e., it is a \mathcal{NG} distribution. The Bayesian updating 165 simplifies to an update of the parameters of the \mathcal{NG} distribution [42, 35]: 166

$$f(\boldsymbol{\theta}|\mathbf{M}) = \mathcal{NG}(\mu_X, \lambda_X | \mu_n, \kappa_n, \alpha_n, \beta_n) = \mathcal{C}_n \lambda_X^{\alpha_n - \frac{1}{2}} \exp\left(-\lambda_X \left(\frac{\kappa_n}{2} \left(\mu_X - \mu_n\right)^2 + \beta_n\right)\right)$$
(9)

¹⁶⁷ where the normalizing constant C_n is given by

$$C_n = \frac{\beta_n^{\alpha_n} \kappa_n^{\frac{1}{2}}}{\Gamma(\alpha_n) \left(2\pi\right)^{\frac{1}{2}}}.$$
(10)

The parameters of the posterior distribution can be obtained with the following 168 set of equations:

$$\mu_n = \frac{\kappa_0 \mu_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}}}{\kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}}},\tag{11}$$

$$\kappa_n = \kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^\mathsf{T},\tag{12}$$

$$\alpha_n = \alpha_0 + \frac{n}{2},\tag{13}$$

$$\beta_n = \beta_0 + \frac{1}{2} \left(\boldsymbol{x}_m \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}} + \frac{\kappa_0 \mu_0^2 \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} - 2\kappa_0 \mu_0 \mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}} - \left(\mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}}\right)^2}{\kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}}} \right)$$
(14)

A derivation of the parameters in Equations (11) to (14) can be found in [7] 170 in the context of Bayesian linear regression. For easier accessibility, we provide 171 the derivations in Appendix A. 172

2.5. Marginal posterior predictive distribution 173

169

Typically, the goal is to make predictions about the quantity of interest 174 X. To this end, one needs the posterior predictive distribution of X, which is 175 obtained by marginalization of the joint PDF of X conditional on θ and the 176 posterior distribution of θ given M. When X is modeled by a single random 177 variable and the measurement points are uncorrelated, the posterior predictive 178 distribution is given as [33, 19, 7]179

$$f(x|\boldsymbol{x}_m) = \int_{\boldsymbol{\Theta}} f(x|\boldsymbol{\theta}) f(\boldsymbol{\theta}|\boldsymbol{x}_m) \,\mathrm{d}\boldsymbol{\theta}, \tag{15}$$

where Θ denotes the domain of definition of θ . The conditional independence 180 between X given $\boldsymbol{\theta}$ and M does no longer hold when X is modeled as an RF. 181 Instead, the posterior and the posterior predictive distribution of X will depend 182 on the spatial location z. In RF theory, the PDF of the RF X(z) at location 183 z is termed marginal (or first order) PDF of X(z). The marginal posterior 184 predictive PDF of X(z), denoted $f(x; z | \mathbf{M})$, is given as 185

$$f(x; \boldsymbol{z} | \mathbf{M}) = \int_{\boldsymbol{\Theta}} f(x; \boldsymbol{z} | \boldsymbol{\theta}, \mathbf{M}) f(\boldsymbol{\theta} | \mathbf{M}) \,\mathrm{d}\boldsymbol{\theta}.$$
(16)

Here, $f(x; z|\theta, \mathbf{M})$ is the marginal PDF of X(z) given θ and \mathbf{M} , which requires an additional updating step. In this step, the prior is the marginal PDF of X(z)given θ , $f(x; z|\theta)$, which is a Gaussian PDF with parameters μ_X and λ_X . The posterior PDF $f(x; z|\theta, \mathbf{M})$ is again a Gaussian PDF with parameters μ''_z and λ''_z , which can be calculated by application of the following updating rules for the conditional Gaussian distribution [15, 36, 3]:

$$\mu_{\boldsymbol{z}}^{\prime\prime} = \mu_X + \boldsymbol{R}_{\boldsymbol{z},m} \boldsymbol{\mathrm{R}}_m^{-1} \left(\boldsymbol{x}_m - \mu_X \boldsymbol{1}_n \right)^{\mathsf{T}}, \qquad (17)$$

$$\lambda_{\boldsymbol{z}}^{\prime\prime} = \lambda_X \left(1 - \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \boldsymbol{R}_{\boldsymbol{z},m}^{\mathsf{T}} \right)^{-1}, \qquad (18)$$

V+ 1

,

where $\mathbf{R}_{\boldsymbol{z},m} : \mathbb{R}^d \to \mathbb{R}^{1 \times n}$ is a row vector function with element *i* defined as $\rho(\boldsymbol{z}, \boldsymbol{z}_{m,i})$ with *n* being the number of measurements and \mathbf{R}_m is given by Equation (8).

The integral in Equation
$$(16)$$
 can be written as follows:

$$f(x; \mathbf{z}|\mathbf{M}) = \int_{\lambda_X=0}^{+\infty} \int_{\mu_X=-\infty}^{+\infty} \mathcal{N}(x|\mu_{\mathbf{z}}'', \lambda_{\mathbf{z}}'') \mathcal{N}(\mu_X|\mu_n, \kappa_n \lambda_X) \mathcal{G}(\lambda_X|\alpha_n, \beta_n) \,\mathrm{d}\mu_X \mathrm{d}\lambda_X$$
(19)

Solution of the integral in Equation (19) results in the following marginal pos-terior predictive PDF:

$$f(x; \boldsymbol{z}|\mathbf{M}) = f_t(x|\mu_{\boldsymbol{z},t}, \lambda_{\boldsymbol{z},t}, \nu_t) = \frac{\Gamma\left(\frac{\nu_t}{2} + \frac{1}{2}\right)}{\Gamma\left(\frac{\nu_t}{2}\right)} \left(\frac{\lambda_{\boldsymbol{z},t}}{\pi\nu_t}\right)^{\frac{1}{2}} \left(1 + \frac{\lambda_{\boldsymbol{z},t}\left(x - \mu_{\boldsymbol{z},t}\right)^2}{\nu_t}\right)^{-\frac{1}{2} - \frac{1}{2}}$$
(20)

where $f_t(x|\mu_t, \lambda_t, \nu_t)$ denotes the PDF of the Student's *t*-distribution with location parameter μ_t , scale parameter λ_t and degrees of freedom ν_t [36].

The spatial functions for the parameters of the posterior predictive Student's *t*-distribution are given in closed form by the following expressions:

$$\mu_{\boldsymbol{z},t} = \mu_n + \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \left(\boldsymbol{x}_m - \mu_n \boldsymbol{1}_n \right)^\mathsf{T}, \qquad (21)$$

$$\lambda_{\boldsymbol{z},t} = \frac{\alpha_n}{\beta_n \left(1 - \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \boldsymbol{R}_{\boldsymbol{z},m}^{\mathsf{T}} + \left(1 - \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} \right)^2 \kappa_n^{-1} \right)}, \qquad (22)$$

$$\nu_t = 2\alpha_n. \tag{23}$$

The parameters μ_n , κ_n , α_n and β_n are obtained following the updating rules in Equations (11) to (14). A detailed derivation of the parameter update can be found in Appendix B.

205 2.6. Posterior predictive random field

The approach presented in Section 2.5 enables predicting the marginal distribution of quantity X at any location $z \in \Omega$ given spatial data **M**. This is useful in cases where the correlation among values of X at different locations needs not be accounted for in further predictions [33]. However, in many cases the spatial dependence of X is required for predictions. In such cases, the joint distribution of X at k different locations is given by the k-th order posterior predictive PDF of X(z):

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = \int_{\boldsymbol{\Theta}} f(\boldsymbol{x}; \mathbf{Z} | \boldsymbol{\theta}, \mathbf{M}) f(\boldsymbol{\theta} | \mathbf{M}) \,\mathrm{d}\boldsymbol{\theta}.$$
(24)

The posterior distribution for the parameter vector $\boldsymbol{\theta}$ is the same as the one appearing in Equation (16). The prior distribution of the RF $X(\boldsymbol{z})$ given $\boldsymbol{\theta}$ is Gaussian and, hence, $f(\boldsymbol{x}; \mathbf{Z} | \boldsymbol{\theta})$ is k-variate Gaussian. Since the updating rules for a conditional Gaussian distribution of Equations (17) and (18) can be extended to the multivariate case, $f(\boldsymbol{x}; \mathbf{Z} | \boldsymbol{\theta}, \mathbf{M})$ is also k-variate Gaussian with mean vector $\boldsymbol{\mu}_{\mathbf{Z}}''$ and precision matrix $\boldsymbol{\Lambda}_{\mathbf{Z}}''$, which can be calculated by the following equations [36]:

$$\boldsymbol{\mu}_{\mathbf{Z}}^{\prime\prime} = \mu_{X} \mathbf{1}_{k}^{\mathsf{T}} + \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_{m}^{-1} \left(\boldsymbol{x}_{m} - \mu_{X} \mathbf{1}_{n} \right)^{\mathsf{T}}, \qquad (25)$$

$$\mathbf{\Lambda}_{\mathbf{Z}}^{\prime\prime} = \lambda_X \left(\mathbf{R}_{\mathbf{Z}} - \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \mathbf{R}_{\mathbf{Z},m}^{\mathsf{T}} \right)^{-1}, \qquad (26)$$

where $\mathbf{R}_{\mathbf{Z},m} : \mathbb{R}^{k \times d} \to \mathbb{R}^{k \times n}$ is a matrix function with element i, j defined as $\rho(\mathbf{z}_i, \mathbf{z}_{m,j})$. $\mathbf{R}_{\mathbf{Z}} : \mathbb{R}^{k \times d} \to \mathbb{R}^{k \times k}$ is a matrix function with element i, j defined as $\rho(\mathbf{z}_i, \mathbf{z}_j)$. \mathbf{R}_m is the matrix containing the correlation of the measurement locations and a potential measurement error, as introduced in Section 2.3. $\mathbf{1}_k$ is a $1 \times k$ vector of ones. Equation (24) takes the following form:

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = \int_{\lambda_X = 0}^{+\infty} \int_{\mu_X = -\infty}^{+\infty} \mathcal{N}\left(\boldsymbol{x}_{\boldsymbol{z}} | \boldsymbol{\mu}_{\mathbf{Z}}^{\prime\prime}, \boldsymbol{\Lambda}_{\mathbf{Z}}^{\prime\prime}\right) \mathcal{N}\left(\mu_X | \mu_n, \kappa_n \lambda_X\right) \mathcal{G}\left(\lambda_X | \alpha_n, \beta_n\right) \mathrm{d}\mu_X \mathrm{d}\lambda_X$$
(27)

The integral in Equation (27) results in the following k-th order posterior predictive PDF

$$f(\boldsymbol{x}; \mathbf{Z}|\mathbf{M}) = f_t(\boldsymbol{x}|\boldsymbol{\mu}_{\mathbf{Z},t}, \boldsymbol{\Lambda}_{\mathbf{Z},t}, \nu_t) = \frac{\Gamma\left(\frac{\nu_t}{2} + \frac{k}{2}\right)}{\Gamma\left(\frac{\nu_t}{2}\right)} \frac{\left(\det\left(\boldsymbol{\Lambda}_{\mathbf{Z},t}\right)\right)^{\frac{1}{2}}}{\left(\pi\nu_t\right)^{\frac{k}{2}}} \left(1 + \frac{\left(\boldsymbol{x} - \boldsymbol{\mu}_{\mathbf{Z},t}\right)\boldsymbol{\Lambda}_{\mathbf{Z},t}\left(\boldsymbol{x} - \boldsymbol{\mu}_{\mathbf{Z},t}\right)^{\mathsf{T}}}{\nu_t}\right)^{-\frac{1}{2} - \frac{\kappa}{2}}$$
(28)

where $f_t(\boldsymbol{x}|\boldsymbol{\mu}_{\mathbf{Z},t}, \boldsymbol{\Lambda}_{\mathbf{Z},t}, \nu_t)$ is the k-variate Student's t-distribution [43, 36]. As in the univariate case, ν_t is a scalar parameter denoting the degrees of freedom. ν_t is given by Equation (23) and the parameters $\boldsymbol{\mu}_{\mathbf{Z},t}$ and $\boldsymbol{\Lambda}_{\mathbf{Z},t}$ are given in closed form:

$$\boldsymbol{\mu}_{\mathbf{Z},t} = \mu_n \mathbf{1}_k^{\mathsf{T}} + \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \left(\boldsymbol{x}_m - \mu_n \mathbf{1}_n \right)^{\mathsf{T}},$$
(29)
$$\boldsymbol{\Lambda}_{\mathbf{Z},t} = \frac{\alpha_n}{\beta_n} \left(\mathbf{R}_{\mathbf{Z}} - \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \mathbf{R}_{\mathbf{Z},m}^{\mathsf{T}} + \left(\mathbf{1}_k^{\mathsf{T}} - \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} \right) \kappa_n^{-1} \left(\mathbf{1}_k^{\mathsf{T}} - \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} \right)^{\mathsf{T}} \right)^{-1}$$
(30)

²³² $\mathbf{R}_{\mathbf{Z}}$, $\mathbf{R}_{\mathbf{Z},m}$ and \mathbf{R}_m follow the definitions for Equations (25) and (26) and the ²³³ parameters μ_n , κ_n , α_n and β_n are obtained following the updating rules in ²³⁴ Equations (11) to (14). The analytical expressions for the parameters of the ²³⁵ multivariate posterior predictive Student's *t*-distribution are derived in detail in ²³⁶ Appendix C.

The multivariate Student's *t*-distribution as predictive distribution for the multivariate Gaussian distribution also appears in Bayesian regression for the normal linear model [35, 7, 44]. In fact, the presented model forms a special case of weighted linear Bayesian regression with a single explanatory variable.

Equation (28) can be used for multivariate predictions of X accounting for the information in **M**. It is noted that for k = 1, Equation (28) reduces to the expression for the marginal posterior predictive Student's t-distribution given in Equation (20), accordingly Equations (29) and (30) reduce to Equations (21)
and (22).

Equations (29) and (30) can be directly transformed to the spatial parameter functions of the posterior predictive RF, i.e., the mean function $\mu_t(\boldsymbol{z})$ and the precision function $\lambda_t(\boldsymbol{z}_1, \boldsymbol{z}_2)$:

$$\mu_t(\boldsymbol{z}) = \mu_n + \boldsymbol{R}_{\boldsymbol{z},m} \boldsymbol{\mathrm{R}}_m^{-1} \left(\boldsymbol{x}_m - \mu_n \boldsymbol{1}_n \right)^\mathsf{T}, \qquad (31)$$

$$\lambda_{t}\left(\boldsymbol{z}_{1},\boldsymbol{z}_{2}\right) = \frac{\alpha_{n}}{\beta_{n}}\left(\rho\left(\boldsymbol{z}_{1},\boldsymbol{z}_{2}\right) - \boldsymbol{R}_{\boldsymbol{z}_{1},m}\boldsymbol{\mathbf{R}}_{m}^{-1}\boldsymbol{R}_{\boldsymbol{z}_{2},m}^{\mathsf{T}} + \left(1 - \boldsymbol{R}_{\boldsymbol{z}_{1},m}\boldsymbol{\mathbf{R}}_{m}^{-1}\boldsymbol{\mathbf{1}}_{n}^{\mathsf{T}}\right)\kappa_{n}^{-1}\left(1 - \boldsymbol{R}_{\boldsymbol{z}_{2},m}\boldsymbol{\mathbf{R}}_{m}^{-1}\boldsymbol{\mathbf{1}}_{n}^{\mathsf{T}}\right)\right)^{-1}$$

$$(32)$$

where $\rho(\boldsymbol{z}_1, \boldsymbol{z}_2)$ is the prior correlation of \boldsymbol{z}_1 and \boldsymbol{z}_2 . $\boldsymbol{R}_{\boldsymbol{z},m}$ and \boldsymbol{R}_m are utilized as in Equations (17) and (18). The posterior predictive RF is fully defined by the parameters specified by Equations (23), (31) and (32).

252 2.7. Choice of correlation parameters

The choice of the prior autocorrelation function $\rho(z_1, z_2)$ has significant in-253 fluence on the predictive distribution of the proposed RF model; it controls the 254 spatial variability of the prior RF and the correlation of the measurement loca-255 tions in \mathbf{R}_m . Hence, the autocorrelation function and its parameters need to be 256 chosen carefully. Although literature is available on different parametric corre-257 lation models, their advantages and disadvantages [e.g. 5, 41, 45], the specific 258 parameter choice for a problem at hand remains challenging if little informa-259 tion about the modeled quantity is available. This problem can be addressed 260 by treating the vector $\boldsymbol{\tau}$ of correlation parameters as a random vector with 261 associated prior distribution $f(\tau)$. The dependency between τ and the multi-262 variate posterior predictive distribution can be expressed explicitly by extending 263 Equation (24) as follows: 264

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}, \boldsymbol{\tau}) = \int_{\boldsymbol{\Theta}} f(\boldsymbol{x}; \mathbf{Z} | \boldsymbol{\theta}, \mathbf{M}, \boldsymbol{\tau}) f(\boldsymbol{\theta} | \mathbf{M}, \boldsymbol{\tau}) \, \mathrm{d}\boldsymbol{\theta}.$$
(33)

 $_{265}$ $f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M})$ can then be determined by marginalization of $f(\boldsymbol{x}; \mathbf{Z}, \boldsymbol{\tau} | \mathbf{M})$:

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = \int_{\mathbf{T}} f(\boldsymbol{x}; \mathbf{Z}, \boldsymbol{\tau} | \mathbf{M}) \, \mathrm{d}\boldsymbol{\tau} = \int_{\mathbf{T}} f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}, \boldsymbol{\tau}) \, f(\boldsymbol{\tau} | \mathbf{M}) \, \mathrm{d}\boldsymbol{\tau}, \qquad (34)$$

- with T denoting the domain of definition of τ . Figure 2 illustrates the adapted
- $_{267}$ hierarchical Bayesian model where τ is considered as additional uncertain parameter, in contrast to the deterministic choice illustrated in Figure 1. The



Figure 2: Adapted hierarchical Bayesian model to consider τ as uncertain parameter. The dependence of the resulting RF model on τ can be integrated out when τ is modeled as random vector.

closed-form updating procedure for the posterior predictive expressions can only be used to find $f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}, \boldsymbol{\tau})$. Direct evaluation of Equation (34) can be cumbersome or even impossible, as it requires evaluation of $f(\boldsymbol{\tau} | \mathbf{M})$, which depends on the choice of the correlation model and most likely cannot be evaluated in closed form.

268

Through application of Bayes' theorem, $f(\boldsymbol{\tau}|\mathbf{M})$ is given by the following expression:

$$f(\boldsymbol{\tau}|\mathbf{M}) \propto f(\boldsymbol{\tau}) \cdot f(\mathbf{M}|\boldsymbol{\tau}).$$
 (35)

²⁷⁶ Including the dependency on τ in the definition of the likelihood function of ²⁷⁷ Equation (2) gives

$$L\left(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau}\right) = \frac{\lambda_X^{\frac{n}{2}}}{\left(2\pi\right)^{\frac{n}{2}}\det\left(\mathbf{R}_m\left(\boldsymbol{\tau}\right)\right)} \exp\left(-\frac{\lambda_X}{2}\left(\boldsymbol{x}_m - \mu_X \mathbf{1}_n\right)\left(\mathbf{R}_m\left(\boldsymbol{\tau}\right)\right)^{-1}\left(\boldsymbol{x}_m - \mu_X \mathbf{1}_n\right)^{\mathsf{T}}\right)$$
(36)

²⁷⁸ $f(\mathbf{M}|\boldsymbol{\tau})$ is the proportionality constant in $f(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau}) \propto f(\boldsymbol{\theta}) \cdot \mathbf{L}(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau})$, hence

$$f(\mathbf{M}|\boldsymbol{\tau}) = \frac{f(\boldsymbol{\theta}) \cdot \mathbf{L}(\boldsymbol{\theta}|\mathbf{M}, \boldsymbol{\tau})}{f(\boldsymbol{\theta}|\mathbf{M}, \boldsymbol{\tau})}.$$
(37)

²⁷⁹ Note that $\boldsymbol{\theta}$ and $\boldsymbol{\tau}$ are independent and thus, $f(\boldsymbol{\theta}|\boldsymbol{\tau}) = f(\boldsymbol{\theta})$. $f(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau})$ is the ²⁸⁰ posterior PDF of $\boldsymbol{\theta}$ for a given $\boldsymbol{\tau}$, which is a \mathcal{NG} PDF with parameters given in ²⁸¹ Section 2.4. Splitting the densities and their respective normalizing constants ²⁸² in Equation (37) gives

$$f(\mathbf{M}|\boldsymbol{\tau}) = \frac{\mathcal{C}_0}{\mathcal{C}_n(\boldsymbol{\tau})} \cdot (2\pi)^{-\frac{n}{2}} \det(\mathbf{R}_m(\boldsymbol{\tau}))^{-\frac{1}{2}} \frac{\hat{f}(\boldsymbol{\theta}) \cdot \hat{\mathbf{L}}(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau})}{\hat{f}(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau})}, \qquad (38)$$

where C_0 and C_n are defined in Equations (4) and (10). $\hat{f}(\boldsymbol{\theta})$ and $\hat{f}(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau})$ are the unnormalized prior and posterior \mathcal{NG} distributions. $\hat{L}(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau})$ is the exponential term of the likelihood function and is equal to the ratio of $\hat{f}(\boldsymbol{\theta}|\mathbf{M},\boldsymbol{\tau})$ and $\hat{f}(\boldsymbol{\theta})$ (cf. Appendix A). Thus, the fraction disappears in Equation (38). Inserting the expressions for C_0 and C_n into Equation (38) yields

$$f\left(\mathbf{M}|\boldsymbol{\tau}\right) = \left(\frac{\kappa_0}{\kappa_n\left(\boldsymbol{\tau}\right)}\right)^{\frac{1}{2}} \frac{\Gamma\left(\alpha_n\right)\beta_0^{\alpha_0}}{\Gamma\left(\alpha_0\right)\left(\beta_n\left(\boldsymbol{\tau}\right)\right)^{\alpha_n}} \left(2\pi\right)^{-\frac{n}{2}} \det\left(\mathbf{R}_m\left(\boldsymbol{\tau}\right)\right)^{-\frac{1}{2}}.$$
 (39)

Using Equation (39), sampling from $f(\boldsymbol{\tau}|\mathbf{M})$ can be achieved, e.g. by using Markov chain Monte Carlo methods [8]. These samples $\boldsymbol{\tau}_i, i = 1, \dots, N_{MCMC}$ can then be used to approximate $f(\boldsymbol{x}; \mathbf{Z}|\mathbf{M})$:

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) \approx \frac{1}{N_{MCMC}} \sum_{i=1}^{N_{MCMC}} f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}, \boldsymbol{\tau}_i).$$
(40)

Alternatively, the posterior distribution of τ can be approximated by its maximum a-posteriori (MAP) estimate [46]. That is, Equation (34) is approximated by

$$f(\mathbf{x}; \mathbf{Z}|\mathbf{M}) \approx f(\mathbf{x}; \mathbf{Z}|\mathbf{M}, \boldsymbol{\tau}^*),$$
 (41)

where τ^* is the MAP estimate of τ . It is found by maximizing Equation (35) with respect to τ . Using Equation (39), this is equivalent to solving the following optimization problem:

$$\arg \max_{\boldsymbol{\tau} \in \mathbf{T}} f(\boldsymbol{\tau}|\mathbf{M}) = \arg \min_{\boldsymbol{\tau} \in \mathbf{T}} \ln \left(\kappa_n\left(\boldsymbol{\tau}\right)\right) + 2\alpha_n \ln \left(\beta_n\left(\boldsymbol{\tau}\right)\right) + \ln \left(\det \left(\mathbf{R}_m\left(\boldsymbol{\tau}\right)\right)\right) - 2\ln \left(f(\boldsymbol{\tau})\right)$$

$$(42)$$

where κ_n , α_n and β_n follow the definitions in Section 2.4 conditional on τ .

The parametric form of the correlation model can be chosen among a set of models by means of Bayesian model selection. To this end, the marginal likelihood, i.e., the normalizing constant of Eq. (35), must be evaluated for the different parametric model choices and multiplied with the prior beliefs in the models [47].

³⁰³ 2.8. Extension to non-Gaussian prior random fields

The presented Bayesian approach is applicable to Gaussian prior RFs and data assigned with additive Gaussian measurement error. Its applicability can be extended to the class of so-called translation RFs, defined as [4, 48]

$$Y(\boldsymbol{z}) = T(U(\boldsymbol{z})), \qquad (43)$$

where $U(\boldsymbol{z})$ is a zero-mean and unit-variance Gaussian RF. If the marginal cumulative distribution function (CDF) of the non-Gaussian RF $F_{Y;\boldsymbol{z}}(y(\boldsymbol{z}))$ is given and it is strictly increasing, one can define the transformation of Equation (43) as $T(\cdot) = F_{Y;\boldsymbol{z}}^{-1}(\Phi(\cdot))$, with $F_{Y;\boldsymbol{z}}^{-1}(\cdot)$ denoting the inverse of $F_{Y;\boldsymbol{z}}(\cdot)$ and $\Phi(\cdot)$ the standard normal CDF [49]. $U(\boldsymbol{z})$ is obtained from $Y(\boldsymbol{z})$ by inversion of Equation (43):

$$U(\boldsymbol{z}) = T^{-1}(Y(\boldsymbol{z})).$$
(44)

To apply the proposed hierarchical Bayesian approach to the non-Gaussian RF Y(z), each measurement outcome $y_{m,i}$ transformed to the Gaussian space through Equation (44) should be associated with an additive Gaussian error. This can be equivalently stated as follows:

$$y_{m,i} = T\left(u\left(\boldsymbol{z}_{m,i}\right) + \varepsilon_i\right),\tag{45}$$

where ε_i is a zero-mean Gaussian measurement error. A special case is a lognormal RF Y(z) with parameters $\mu_{\ln Y}$ and $\lambda_{\ln Y}$ and a multiplicative lognormal measurement error, i.e., $y_{m,i} = y(z_{m,i}) \cdot \varepsilon_{y,i}$. In such case, Equations (43) and (45) can be rewritten as functions of a Gaussian RF X(z):

$$Y (\boldsymbol{z}) = \exp (X (\boldsymbol{z})),$$

$$y_{m,i} = \exp (x (\boldsymbol{z}_{m,i}) + \varepsilon_i) = \exp (x (\boldsymbol{z}_{m,i})) \cdot \exp (\varepsilon_i) = \exp (x (\boldsymbol{z}_{m,i})) \cdot \varepsilon_{y,i}.$$
(47)

 $\mu_{\ln Y}$ and $\lambda_{\ln Y}$ are the mean value and precision respectively of the underlying 321 Gaussian RF X(z) including the precision of the measurement error, i.e., $\mu_X =$ 322 $\mu_{\ln Y}$ and $\lambda_X = \lambda_{\ln Y}$. As defined in Section 2.3, λ_X is given as the overall 323 precision of $X(z) + \varepsilon$. The error term $\varepsilon_{y,i}$ follows a lognormal distribution with 324 median 1. Its parameters are $\mu_{\ln\varepsilon} = 0$ and $\lambda_{\ln\varepsilon} = \frac{\lambda_X}{\gamma_{\varepsilon}}$, which are mean value and 325 precision respectively of the underlying Gaussian measurement error. γ_{ε} has to 326 be chosen accordingly to reflect the contribution of ε to the overall variance of the 327 underlying Gaussian random field. That is, the hierarchical Bayesian approach 328 is directly applicable by a simple logarithmic transformation of the data and 329 the measurement error. After the updating procedure, the posterior predictive 330 RF can be transformed back to the original space by applying Equation (46). 331 The transformed marginal distribution of the posterior predictive RF has the 332 form of a log-Student's t-distribution. This distribution model is used in finance 333 for the pricing of options [50, 51] and belongs to the family of log-symmetric 334 distributions [52]. The marginal PDF of the posterior predictive RF is defined 335 as follows: 336

$$f\left(y;\boldsymbol{z}|\mathbf{M}\right) = f_{t,\ln}\left(y|\mu_{\boldsymbol{z},t},\lambda_{\boldsymbol{z},t},\nu_{t}\right) = y^{-1} \frac{\Gamma\left(\frac{\nu_{t}}{2} + \frac{1}{2}\right)}{\Gamma\left(\frac{\nu_{t}}{2}\right)} \left(\frac{\lambda_{\boldsymbol{z},t}}{\pi\nu_{t}}\right)^{\frac{1}{2}} \left(1 + \frac{\lambda_{\boldsymbol{z},t}\left(\ln\left(y\right) - \mu_{\boldsymbol{z},t}\right)^{2}}{\nu_{t}}\right)^{-\frac{\nu_{t}}{2} - \frac{1}{2}}$$

$$(48)$$

The finite-dimensional PDF can be derived in a similar manner. It is noted that the log-Student's *t*-distribution has divergent integer moments of any order. A short proof of this can be found in Appendix D. The parametrization of Y(z)conditional on **M** is done by means of $\mu_{z,t}$, $\lambda_{z,t}$ and ν_t , i.e., in terms of the parameters of the underlying Student's *t*-RF X(z). For $\nu_t \to \infty$, $f_{t,\ln}(y_z|\mathbf{M})$ converges to a lognormal distribution with location parameter $\mu_{z,t}$ and scale parameters $\lambda_{z,t}^{-\frac{1}{2}}$.

³⁴⁴ 2.9. Sampling the posterior predictive random field

The finite-dimensional distribution of the posterior predictive RF is the multivariate Student's t-distribution with parameters $\mu_{\mathbf{Z},t}, \Lambda_{\mathbf{Z},t}$ and ν_t . The posterior predictive random vector $\mathbf{X}(\mathbf{Z})$ corresponding to locations \mathbf{Z} can be expressed as follows [43]:

$$\mathbf{X}(\mathbf{Z}) = \frac{\mathbf{U}(\mathbf{Z})}{\sqrt{\frac{V}{\nu_t}}} + \boldsymbol{\mu}_{\mathbf{Z},t},\tag{49}$$

where $U(\mathbf{Z})$ is a zero-mean Gaussian random vector with precision matrix $\Lambda_{\mathbf{Z},t}$. 349 V is a random variable that follows the chi-square distribution with ν_t degrees 350 of freedom and is independent of $U(\mathbf{Z})$. Replacing $U(\mathbf{Z})$ in Equation (49) by 351 $U(\boldsymbol{z})$, a zero-mean Gaussian RF with spatial precision function $\lambda_t(\boldsymbol{z}_1, \boldsymbol{z}_2)$ as 352 given by Equation (32), and furthermore replacing $\mu_{\mathbf{Z},t}$ by $\mu_t(\mathbf{z})$, the spatial 353 function for the mean value defined in Equation (31), yields the corresponding 354 expression for the posterior predictive Student's t-RF. Hence, the Student's t-355 RF X(z) can be expressed as a function of a Gaussian RF and one additional 356 independent chi-square random variable. In case of sampling from a translation 357 RF Y(z), the transformation of Equation (43) has to be adapted accordingly. 358 Samples from U(z) can be generated by a variety of existing methods [e.g. 6]. 350

2.10. Connection to the Bayesian approach of EN 1990

Annex D.7 of EN 1990 (Eurocode 0) on the basis of structural design of-361 fers a method to determine design values for material properties when samples 362 are available [34]. The samples are used to estimate a quantile value of the 363 underlying probability distribution, the so-called characteristic value. This ap-364 proach distinguishes between the cases where (a) mean and variance of the 365 material property are unknown and (b) only its variance is unknown. In case 366 (a), the characteristic value can be estimated based on the sample mean, sam-367 ple standard deviation and the number of samples n. The underlying theory 368 is a Bayesian approach and the calculated value is the 5% quantile value of 369 the posterior predictive distribution [33, 2]. We show in the following that the 370

³⁷¹ hierarchical approach presented in this paper is a generalization of case (a) in
³⁷² Annex D.7 of EN 1990.

We consider a material property X that follows a normal distribution with unknown parameters $\boldsymbol{\theta}$ and that a set of samples $\boldsymbol{x}_m = [x_{m,1}, x_{m,2}, \dots, x_{m,n}]^{\mathsf{T}}$ are available. If no prior information about $f(\boldsymbol{\theta})$ is available, a non-informative choice can be made by choosing a \mathcal{NG} distribution with the following parameters [42]:

$$[\mu_0, \kappa_0, \alpha_0, \beta_0] = \left[/, 0, -\frac{1}{2}, 0 \right],$$
(50)

resulting in $f(\boldsymbol{\theta}) = \lambda_X^{-1}$.

Furthermore, we assume independence of the random variables corresponding to the measurement locations and neglect the measurement error, i.e., $\mathbf{R}_m =$ **I**. This leads to a simplification of Equations (11) to (14):

$$\mu_n = \frac{\mathbf{1}_n \boldsymbol{x}_m^{\mathsf{T}}}{n} = \frac{1}{n} \sum_{i=1}^n x_{m,i},\tag{51}$$

$$\kappa_n = n,\tag{52}$$

$$\alpha_n = \frac{n-1}{2},\tag{53}$$

$$\beta_n = \frac{1}{2} \left(\boldsymbol{x}_m \boldsymbol{x}_m^{\mathsf{T}} - \frac{\left(\mathbf{1}_n \boldsymbol{x}_m^{\mathsf{T}} \right)^2}{n} \right) = \frac{1}{2} \sum_{i=1}^n \left(x_{m,i} - \mu_n \right)^2.$$
(54)

If one neglects the dependence between the measurements and the RF at the predictive locations, the posterior predictive distribution $f(x|x_m)$ is obtained following Equation (15) and is space-invariant. It is a Student's t-distribution with the following parameters:

$$\mu_t = \mu_n = \frac{1}{n} \sum_{i=1}^n x_{m,i},\tag{55}$$

$$\lambda_t = \frac{\alpha_n}{\beta_n \left(1 + \kappa_n^{-1}\right)} = \frac{n(n-1)}{(n+1)\sum_{i=1}^n \left(x_{m,i} - \mu_n\right)^2},$$
(56)

$$\nu_t = 2\alpha_n = n - 1. \tag{57}$$

The characteristic values in the method in EN 1990 are defined as 5% quantile values of a Student's *t*-distribution with parameters given by Equations (55) to (57). An additional transformation step is added for ease of use, in which the Student's *t*-distributed random variable X is normalized:

$$U_t = (X - \mu_t) \lambda^{\frac{1}{2}}, \tag{58}$$

where U_t follows the standard Student's *t*-distribution with ν_t degrees of freedom, i.e., $\mu_t = 0$ and $\lambda_t = 1$. This normalization allows the use of standardized coefficients (k_n values), which only depend on *n*:

$$k_n = -F_{U_t}^{-1}(p)\sqrt{\frac{n+1}{n}},\tag{59}$$

where $F_{U_t}^{-1}(\cdot)$ is the inverse CDF of U_t and p = 0.05, since the characteristic value x_k is defined as the 5% quantile value. Using the k_n value, x_k is obtained as follows:

$$x_k = \bar{\mu}_X \left(1 - k_n \bar{\delta}_X \right), \tag{60}$$

where $\bar{\mu}_X = \frac{1}{n} \sum_{i=1}^n x_{m,i}$ is the sample mean and $\bar{\delta}_X = \frac{\bar{\mu}_X}{\bar{\sigma}_X}$ is the sample coefficient of variation with $\bar{\sigma}_X = \frac{1}{n-1} \sum_{i=1}^n (x_{m,i} - \bar{\mu}_X)^2$. EN 1990 provides tabulated values of k_n for varying n.

The method in EN 1990 also covers the case when the material property 399 Y follows a lognormal distribution and $\boldsymbol{y}_m = \left[y_{m,1}, y_{m,2}, \ldots, y_{m,n}\right]^\mathsf{T}$ are the 400 available samples. In this case, the Bayesian analysis underlying the method 401 is conducted as described above for the Gaussian random variable $X = \ln(Y)$ 402 with the logarithmic samples $x_{m,i} = \ln(y_{m,i}), i = 1, \ldots, n$. The posterior 403 predictive distribution $f(y|\boldsymbol{y}_m)$ is a log-Student's t-distribution parameterized 404 in terms of the parameters of the underlying Student's t-distribution given by 405 Equations (55) to (57). The characteristic value y_k is the 5% quantile value of 406 $f(y|\boldsymbol{y}_m)$, which is equivalent to the exponential of the 5% quantile value of the 407 underlying Student's t-distribution. Thus, y_k can be calculated as 408

$$y_k = \exp\left(\bar{\mu}_X \left(1 - k_n \bar{\delta}_X\right)\right),\tag{61}$$

where $\bar{\mu}_X$ and $\bar{\delta}_X$ are the sample mean and sample coefficient of variation of the logarithmic samples and k_n is given by Equation (59).

In a nutshell, the method in Annex D.7 of EN 1990 to determine characteristic values for the design of structures is a special case of the presented RF analysis, which assumes a non-informative prior distribution, independent measurements without measurement error and independence between measurement locations and the material parameter at the predictive locations.

416 3. Numerical examples

In this section, the proposed approach is applied to two numerical examples. The first one involves a one-dimensional RF of a geotechnical material, while the second one models the concrete compressive strength of a ship lock wall with a two-dimensional anisotropic RF.

421 3.1. Tip resistance of cohesive soil

Soil parameters are often determined based on measurements from cone 422 penetration testing (CPT). In CPT, the tip resistance q_T measures the force 423 required to push the cone through the soil and can be used to infer further 424 soil parameters. In this example, data from a CPT is used, where the tip 425 resistance of a cohesive soil layer was measured in depths from z = 3.900 m to 426 $z = 10.275 \,\mathrm{m}$ resulting in 256 equidistant measurements of the tip resistance. 427 The data is taken from [53] and was also used by Wang and Zhao to illustrate 428 the performance of Bayesian compressive sampling when sparse data is available 429 [26]. The tip resistance is modeled by the one-dimensional RF $q_T(z)$ in vertical 430 direction with lognormal prior marginal distribution. Hence, the transformation 431 of Equation (46) is applied: 432

$$q_T(z) = \exp\left(X(z)\right). \tag{62}$$

⁴³³ The underlying prior RF X(z) is a homogeneous Gaussian RF with unknown ⁴³⁴ mean value μ_X and unknown precision λ_X . The prior autocorrelation function $_{435}$ is modeled by the exponential model with unknown correlation length l_c :

$$\rho(z_i, z_j) = \exp\left(-\frac{|z_j - z_i|}{l_c}\right) \tag{63}$$

Furthermore, no prior information on μ_X or λ_X are available and thus a noninformative prior \mathcal{NG} distribution is chosen with the parameters from Equation (50).

It is assumed that knowledge of the full data set is not available but only a 439 subset of 13 measurement values taken at equidistant locations, as illustrated by 440 the blue dots in panel a) of Figure (3). It is assumed that the measurements are 441 associated with a multiplicative lognormal measurement error, where the por-442 tion of the total variance attributed to the transformed Gaussian measurement 443 error is given as $\gamma_{\varepsilon} = 0.01$. In a first step, the MAP estimate for l_c is obtained 444 by solving the minimization problem of Equation (42), where the vector $\boldsymbol{\tau}$ only 445 consists of l_c . A uniform prior on the positive numbers is employed for l_c and 446 hence the term $\ln(f(\boldsymbol{\tau}))$ in the optimization problem can be dropped and the 447 MAP estimate reduces to a maximum likelihood estimate [54]. The resulting 448 estimate for l_c is obtained as $l_c^* = 0.74$ m. 449

Consequently, the posterior parameters of the \mathcal{NG} distribution are obtained 450 by application of Equations (11) to (14) in combination with Equation (47) to 451 account for the log-transformation of the measurements. The spatial parameter 452 functions of the posterior predictive Student's t-RF are calculated by means 453 of Equations (31) and (32). From Equation (23) the degrees of freedom are 454 calculated as $\nu_t = 12$. These are the parameters of the RF $q_T(z)$ given **M**, which 455 has log-Student's t-marginal distribution with PDF given by Equation (48). As 456 the moments are not defined, the illustration in panel a) of Figure (3) shows the 457 median of the posterior predictive tip resistance and the corresponding 5% and 458 95% quantile values along the depth of the soil layer. The increasing width of the 459 orange area shows that the uncertainty is very small close to the measurement 460 locations and increases away from the measurements. The full data set of 256 461 measurements is indicated by a black dotted line. Panel b) of Figure 3 shows 462 three independent realizations of the posterior predictive RF. Comparison of the 463



Figure 3: Posterior predictive RF of the tip resistance $q_{\rm T}$. Panel a) shows the median (red line) and the two-sided 90% credible interval, i.e., the area between the 5% and 95% quantile value (orange area) of the marginal log-Student's *t*-distributions. The 13 blue dots mark the used measurement locations and values while the full data set is illustrated by the dotted black line. Panel b) shows three independent realizations of the posterior predictive RF in comparison to the two-sided 90% credible interval in gray.

random realizations with the full data set shows good accordance regarding the
number and amplitude of strong local deviations from the posterior predictive
median. Hence, the proposed approach can sufficiently approximate both the
overall trend of the RF and the associated uncertainty.

To illustrate the influence of the number of measurements on the posterior 468 prediction, the above calculations are repeated for n = 6 and n = 64 equidis-469 tant measurements. Figure 4 illustrates the measurement values and locations 470 by blue dots in panel a) and panel c), respectively. For n = 6, the MAP op-471 timization results in $l_{c,6}^* = 3.89 \,\mathrm{m}$ and for n = 64 it gives $l_{c,64}^* = 1.17 \,\mathrm{m}$. This 472 large difference in the MAP estimates is due to the assumed uninformative prior 473 distribution for the correlation length, in which case, the MAP estimate only 474 depends on the data. Large differences in the data can lead to significant varia-475 tion in the estimated correlation length. The median and corresponding 5% and 476 95% quantile values of $q_T(z)$ are illustrated in panel a) and c), respectively of 477 Figure 4. Comparison to Figure 3 shows that with increasing amount of data, 478



Figure 4: Posterior predictive RF of the tip resistance $q_{\rm T}$ for n = 6 (panel a) and b)) and n = 64 (panel c) and d)). Panel a) and c) show the median (red line) and the two-sided 90% credible intervals of the marginal log-Student's *t*-distributions. The blue dots mark the used measurement locations and values while the full data set is illustrated by the dotted black line. Panel b) and c) each show three independent realizations of the posterior predictive RF in comparison to the two-sided 90% credible intervals in gray.

the uncertainty, i.e., the variability of $q_T(z)$ is reduced. However, even with 479 a small amount of data (n = 6), the global trend of the tip resistance can be 480 predicted and the location-specific information can be used efficiently to set up 481 an RF model. The large variability in the areas between the measurements is 482 illustrated by three independent realizations in panel b) of Figure 4. When the 483 amount of data is relatively large (n = 64), the remaining uncertainty in the 484 tip resistance becomes comparatively small and random realizations of the RF 485 do not differ significantly from the full data set, as can be seen in panel d) of 486 Figure 4. 487

Figure 5 plots $f(l_c|\mathbf{M})$ with the MAP estimate $l_c^* = 0.74$ m located at the mode of $f(l_c|\mathbf{M})$. It appears that, although the posterior distribution has a distinct mode, it covers a broad range by remaining relatively flat for increasing values of l_c . This is caused by the uniform prior distribution for l_c and shows that such a uniform prior can lead to an improper posterior distribution of the correlation length. While this is not a problem when using MAP, it is an issue



Figure 5: Posterior distribution of the correlation length $f(l_c|\mathbf{M})$ as function of the correlation length l_c and the corresponding MAP estimate l_c^* .

when the full posterior distribution of l_c is to be used. In such cases, a different prior distribution should be chosen.

⁴⁹⁶ 3.2. Concrete compressive strength of a ship lock wall

In this example, we investigate the concrete compressive strength f_c of a 497 ship lock wall made of tamped concrete in the 1920s. The length of the wall is 498 105 m and the height of the tamped concrete layer is 8 m, the third dimension 499 is not taken into account for this study. 24 measurements of f_c are available 500 from three vertical core samples taken at the quarter points of the wall [2]. The 501 situation is illustrated in Figure 6 and the measurement data and corresponding 502 locations are shown in Table 1. We assume that the measurements are associated 503 with a multiplicative lognormal measurement error with coefficient of variation 504 $CV_{\varepsilon} = 0.025.$



Figure 6: Ship lock wall with a total length of 105 m and a total height of 8 m made of tamped concrete from the 1920s. Three vertical core samples (C_1 , C_2 and C_3) were taken at the quarter points of the wall indicated by the three dashed lines.

505 506

Applying the transformation of Equation (46), the logarithm of f_c is modeled

Core sample C_1			Core sample C_2			Core sample C_3		
$z_1 [\mathrm{m}]$	$z_2 [\mathrm{m}]$	$f_{\rm c,m}$ [MPa]	$z_1 [\mathrm{m}]$	$z_2 [\mathrm{m}]$	$f_{\rm c,m}$ [MPa]	$z_1 [\mathrm{m}]$	$z_2 [\mathrm{m}]$	$f_{\rm c,m}$ [MPa]
26.25	0.40	29.2	52.5	0.21	21.2	78.75	0.34	18.5
	1.24	15.5		1.25	16.0		1.34	10.3
	2.25	8.7		2.05	32.0		2.17	13.2
	3.15	12.3		3.33	20.7		3.24	14.5
	4.12	16.2		4.15	13.8		4.27	25.4
	5.33	11.6		5.25	12.1		5.12	14.5
	6.15	13.4		6.40	8.6		6.23	13.2
	7.05	13.9		7.45	14.8		7.08	33.0

Table 1: Measurements of the concrete compressive strength f_c and the corresponding measurement locations of 24 specimens from 3 vertical core samples $(C_1, C_2 \text{ and } C_3)$ in the quarter points of the ship lock wall.

 $_{507}$ with a two-dimensional Gaussian RF with non-informative prior \mathcal{NG} distribu-

tion (cf. Equation (50)).

Typically, massive concrete structures made of tamped concrete from that time have been built in layers [55]. Hence, we employ a transverse anisotropic exponential correlation function, where the correlation length $l_{c,1}$ in direction z_1 differs from the correlation length $l_{c,2}$ in direction z_2 [56]:

$$\rho\left(\boldsymbol{z}_{i}, \boldsymbol{z}_{j}\right) = \exp\left(-\sqrt{\frac{\left(\Delta_{1}\left(\boldsymbol{z}_{i}, \boldsymbol{z}_{j}\right)\right)^{2}}{l_{c,1}^{2}} + \frac{\left(\Delta_{2}\left(\boldsymbol{z}_{i}, \boldsymbol{z}_{j}\right)\right)^{2}}{l_{c,2}^{2}}}\right),\tag{64}$$

where $\Delta_1(\boldsymbol{z}_i, \boldsymbol{z}_j)$ and $\Delta_2(\boldsymbol{z}_i, \boldsymbol{z}_j)$ denote the canonical distances of \boldsymbol{z}_i and \boldsymbol{z}_j in directions \boldsymbol{z}_1 and \boldsymbol{z}_2 respectively. Assuming a uniform prior on $l_{c,1}$ and $l_{c,2}$ results in the following MAP estimate for the two correlation lengths:

$$\boldsymbol{l}_{c}^{*} = \begin{bmatrix} l_{c,1}^{*}, \ l_{c,2}^{*} \end{bmatrix} = \begin{bmatrix} 1.54 \,\mathrm{m}, 0.58 \,\mathrm{m} \end{bmatrix}$$
(65)

These values are used in the Bayesian updating to obtain the posterior predictive RF for f_c . As the marginal posterior predictive PDF is a log-Student's *t*distribution, the moments cannot be evaluated and thus, Figure 7 illustrates the median (panel a)) and the corresponding 5% quantile value (panel b)) of $f_c(z)$



Figure 7: Posterior predictive median (panel a)) and 5% quantile value (panel b)) of the concrete compressive strength f_c of a ship lock wall obtained with data from three vertical core samples (n = 24 measurements of the concrete compressive strength). The median and 5% quantile value at points A, B and C are listed in Table 2.

given M across the ship lock wall. The measured values and the information about their location are clearly reflected, as regions close to low measurement values show low median and 5% quantile values, and regions close to high measurement values show higher median and 5% quantile values. This is illustrated by the example of three points (A, B and C) at different locations of the ship lock wall, where the median and 5% quantile values have been extracted and listed in Table 2. Point A, located close to a low measurement value, features

Table 2: Median (50% quantile value, $f_{c,0.5}$) and 5% quantile value ($f_{c,0.05}$) of the marginal posterior predictive concrete compressive strength at three different locations (A, B and C) of the ship lock wall.

	z_1 [m]	$z_2 [\mathrm{m}]$	$f_{c,0.5}$ [MPa]	$f_{c,0.05}$ [MPa]
Point A	25.95	2.5	10.7	6.6
Point B	37.25	5.3	15.9	8.2
Point C	78.3	6.85	23.1	14.1

526

a posterior median of 10.7 MPa and a 5% quantile value of 6.6 MPa, both of which are significantly lower than those at point C with a median of 23.1 MPa and a 5% quantile value of 14.1 MPa. Contrary to point A, point C is located close to a high measurement value (cf. Table 1). The median of 15.9 MPa and 531 5% quantile of 8.2 MPa at point B are representative values for all locations far 532 away from the measurements, i.e., all points with negligible spatial correlation 533 to any measurement location.

Section 2.10 demonstrates the connection of the proposed RF approach and 534 the established Bayesian approach in EN 1990. Next, we compare this approach 535 to the results of the proposed hierarchical RF model using the data of Table 1. 536 The mean and standard deviation of the log-transformed measurement values 537 are $\bar{\mu}_X = 2.75$ and $\bar{\sigma}_X = 0.37$ with a corresponding k_n value of $k_n(n_m = 24) =$ 538 1.75. Applying Equation (61) gives a characteristic value (5% quantile value) of 539 $f_{c,k}=8.2\,\mathrm{MPa}.$ This value matches the 5% quantile value at locations without 540 spatial correlation to the measurement points (cf. point C in Table 2). We note 541 that this congruence depends on the chosen prior parameters of the RF and, 542 thus, is the exception, not the rule. 543

The correlation length is an important parameter in any RF model. To 544 illustrate this, the Bayesian analysis has been carried out for $l_c = 0.5 l_c^*$ and $l_c =$ 545 $2l_c^*$. The resulting marginal median of $f_c(z)$ in the area around the core sample 546 C_2 is illustrated in Figure 8. Obviously, the larger the correlation length, the 547 bigger the area that is influenced by the spatial correlation to the measurements. 548 For $l_c = 0.5 l_c^*$ the spatial effect of the measurements on the median is restricted 549 to a domain of length $\approx 2 \,\mathrm{m}$, wheres for $l_c = 2 l_c^*$ this effect spans over a length 550 of ≈ 10 m. It is mentioned that this is the effect of the final step of the Bayesian 551 approach, where the posterior predictive distribution is obtained. The whole 552 RF is influenced by the data and the chosen correlation length by the global 553 posterior parameters of the \mathcal{NG} distribution, as can be seen by the different 554 median values of $f_c(z)$ at locations D_a , D_b and D_c indicated in Figure 8. These 555 locations are chosen exemplarily for all points with negligible spatial correlation 556 to any measurement location. For $l_c = 0.5 l_c^*$ the median is 15.7 MPa and for 557 $l_c = 2l_c^*$ it is 16.3 MPa, compared to 15.9 MPa when $l_c = l_c^*$. 558

⁵⁵⁹ When employing the MAP procedure to approximate $f(\tau | \mathbf{M})$, it is important to be aware of the sensitivity of the estimate and the amount of information ⁵⁶¹ provided by the data. In this example, the vertical distance of the measurement



Figure 8: Posterior predictive median of the concrete compressive strength of a ship lock wall in the area around core sample C_2 obtained with varying correlation lengths.



Figure 9: Two-dimensional posterior distribution of the correlation lengths in z_1 (horizontal) and z_2 (vertical) direction, $f(\mathbf{l}_c|\mathbf{M})$. The maximum of $f(\mathbf{l}_c|\mathbf{M})$ is located at $l_{c,1} = 1.54$ m and $l_{c,2} = 0.58$ m, which is equivalent to the MAP estimate \mathbf{l}_c^* .

locations is relatively small while the horizontal distance is either 0 or very large. 562 Hence, the MAP estimate for $l_{c,1}$ is subject to larger uncertainty than the MAP 563 estimate for $l_{c,2}$, which is illustrated in Figure 9. While $f(\tau|\mathbf{M})$ has a distinct 564 maximum in direction $l_{c,2}$ at $l_{c,2} = 0.58$ m, it is relatively flat in direction $l_{c,1}$. In 565 fact, any $l_{c,1}$ smaller than 5 m is approximately equally likely given the data at 566 hand. Only for $l_{c,1} > 5$ m the measurements of different core samples are notice-567 ably correlated. This behavior is of special interest when no prior information 568 on the correlation length is assumed, since in such case the MAP estimate is 569 only controlled by the data. In general, learning the correlation length from 570 limited amount of data is not a trivial task, especially if no prior information on 571 the RF parameters is available. In a study on the correlation length of soil pa-572 rameters, a minimum of 5 measurement values within one correlation length are 573 recommended for learning the correlation length of the exponential correlation 574 model [57]. 575

576 4. Conclusion

This paper presents a comprehensive hierarchical Bayesian approach to model 577 random material properties with spatially distributed data. It is based on mod-578 eling a Gaussian random field assuming a normal-gamma prior distribution on 579 its parameters. Closed-form expressions for the posterior normal-gamma dis-580 tribution of the parameters of the random field are derived by making use of 581 the conjugacy of the normal-gamma distribution and a multivariate Gaussian 582 likelihood function. Subsequently, closed-form expressions for the spatial pa-583 rameter function of the posterior predictive random field are derived, resulting 584 in a non-homogeneous Student's t-random field. That is, the marginal distribu-585 tion of the posterior predictive random field is a Student's t-distribution with 586 location-specific parameters. 587

Sampling from such a random field can be achieved by expressing the Student's *t*-random field in terms of a Gaussian random field and one additional chi-squared random variable. For estimating the correlation parameters, a maximum a-posteriori estimation approach is proposed that accounts for the available data and potential prior information. In addition, an extension of the approach to non-Gaussian translation prior random fields is discussed and closed-form expressions for the case of a lognormal marginal prior distribution are derived.

The applicability of the presented approach to different engineering fields is 595 illustrated by two examples, one from the field of geotechnical engineering and 596 one from structural engineering. The derived posterior random field models 597 reflect the location-specific information from the measurements, whereas their 598 uncertainty increases with increasing distance from the measurement locations. 599 Furthermore, it is demonstrated that the uncertainty can be reduced by in-600 creasing the amount of data. The spatial fluctuation of the posterior random 601 field is sensitive to the choice of the correlation length parameter. When no 602 603 information is available on the prior autocorrelation function, the maximum a-posteriori estimate for the correlation length is sensitive to the measurement 604 data and should be handled with care, especially in the case where limited data 605

606 is available.

A measurement error can be included to account for uncertainty in the measurements, in which case the variance contribution of the error to the total random field variance needs to be specified. This contribution can be learned from the data in a similar way as the parameters of the correlation model, which remains a topic of future investigations.

The presented modeling approach can be extended to account for a trend function in the prior random field parameters. A trend in the prior mean can be included by employing a linear basis function model, similar to the work of [23]. A parametric dependence can also be included in the prior precision parameter, which leads to a model known as weighted Bayesian linear regression [7]. Investigation of these models in the context of material modeling is left to future studies.

619 Acknowledgments

This work has been financially supported by the *Bundesanstalt für Wasserbau* (Federal Waterways Engineering and Research Institute, Germany). The corresponding author would like to thank Claus Kunz from the *Bundesanstalt für Wasserbau* who motivated the idea to develop the presented approach and Prof. Lori Graham-Brady from Johns Hopkins University for many discussions that have considerably enhanced the quality of the paper.

626 Appendix A. The posterior normal-gamma distribution

The posterior parameters of the normal-gamma distribution for the parameter vector $\boldsymbol{\theta} = [\mu_X, \lambda_X]^{\mathsf{T}}$, as specified in Equations (11) to (14) are derived in the following.

According to Bayes' theorem, the posterior distribution $f(\boldsymbol{\theta}|\mathbf{M})$ is proportional to the product of prior distribution $f(\boldsymbol{\theta})$ and likelihood $L(\boldsymbol{\theta}|\mathbf{M})$, which are defined in Equations (3) and (5). Using the normal-gamma prior distribution ⁶³³ and the multivariate Gaussian likelihood gives the following expression:

$$f\left(\boldsymbol{\theta}|\mathbf{M}\right) \propto \lambda_{X}^{\alpha_{0}+\frac{n}{2}-\frac{1}{2}} \cdot \exp\left(-\frac{\kappa_{0}\lambda_{X}}{2}\left(\mu_{X}-\mu_{0}\right)^{2}\right) \cdot \exp\left(-\lambda_{X}\beta_{0}\right) \cdot \\ \cdot \exp\left(-\frac{\lambda_{X}}{2}\left(\boldsymbol{x}_{m}-\mu_{X}\mathbf{1}_{n}\right)\mathbf{R}_{m}^{-1}\left(\boldsymbol{x}_{m}-\mu_{X}\mathbf{1}_{n}\right)^{\mathsf{T}}\right).$$
(A.1)

With the definition of $\mathbf{A} = \kappa_0 (\mu_X - \mu_0)^2 - 2\mu_X \mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}} + \mu_X^2 \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}}$, Equation (A.1) can be rearranged as

$$f(\boldsymbol{\theta}|\mathbf{M}) \propto \lambda_X^{\alpha_0 + \frac{n}{2} - \frac{1}{2}} \cdot \exp\left(-\lambda_X \left(\beta_0 + \frac{1}{2}\boldsymbol{x}_m \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}} + \frac{1}{2}\mathbf{A}\right)\right).$$
(A.2)

⁶³⁶ Initially, the focus lies on **A** which is expanded and modified as follows:

$$\mathbf{A} = \left(\kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}}\right) \left(\mu_X^2 - 2\mu_X \frac{\kappa_0 \mu_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{x}_m^{\mathsf{T}}}{\kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}}}\right) + \kappa_0 \mu_0^2.$$
(A.3)

637 Next, the square of the expression inside the second parenthesis is completed:

$$\mathbf{A} = \underbrace{\left(\kappa_{0} + \mathbf{1}_{n}\mathbf{R}_{m}^{-1}\mathbf{1}_{n}^{\mathsf{T}}\right)\left(\mu_{X} - \frac{\kappa_{0}\mu_{0} + \mathbf{1}_{n}\mathbf{R}_{m}^{-1}\boldsymbol{x}_{m}^{\mathsf{T}}}{\kappa_{0} + \mathbf{1}_{n}\mathbf{R}_{m}^{-1}\mathbf{1}_{n}^{\mathsf{T}}}\right)^{2}}_{\mathbf{B}} + \underbrace{\kappa_{0}\mu_{0}^{2} - \frac{\left(\kappa_{0}\mu_{0} + \mathbf{1}_{n}\mathbf{R}_{m}^{-1}\boldsymbol{x}_{m}^{\mathsf{T}}\right)^{2}}{\kappa_{0} + \mathbf{1}_{n}\mathbf{R}_{m}^{-1}\mathbf{1}_{n}^{\mathsf{T}}}}_{\mathbf{C}}$$

$$(A.4)$$

.

The terms of **C** in Equation (A.4) are expanded and converted to a common denominator:

$$\mathbf{C} = \left(\kappa_0 \mu_0^2 \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} - 2\kappa_0 \mu_0 \mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}} - \left(\mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}}\right)^2\right) \left(\kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}}\right)^{-1}.$$
(A.5)

 $_{640}$ Inserting the expression for **B** and **C** into Equation (A.2) gives:

$$f(\boldsymbol{\theta}|\mathbf{M}) \propto \lambda_X^{\alpha_0 + \frac{n}{2} - \frac{1}{2}} \cdot \exp\left(-\lambda_X \left(\beta_0 + \frac{1}{2}\boldsymbol{x}_m \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}} + \frac{1}{2} \mathbf{C}\right)\right) \cdot \exp\left(-\frac{\lambda_X}{2} \mathbf{B}\right).$$
(A.6)

The parametric form of the posterior normal-gamma distribution as defined in
Section 2.4 is as follows:

$$\mathcal{NG}\left(\mu_{X},\lambda_{X}|\mu_{n},\kappa_{n},\alpha_{n},\beta_{n}\right) = \mathcal{C}_{n}\lambda_{X}^{\alpha_{n}-\frac{1}{2}} \cdot \exp\left(-\frac{\kappa_{n}\lambda_{X}}{2}\left(\mu_{X}-\mu_{n}\right)^{2}\right) \cdot \exp\left(-\lambda_{X}\beta_{n}\right).$$
(A.7)

⁶⁴³ Writing out all the terms in Equation (A.6) and comparing it to (A.7) one ⁶⁴⁴ can see that up to the normalizing constant C_n , the resulting expression of ⁶⁴⁵ Equation (A.6) is a normal-gamma distribution with parameters as follows:

$$\mu_n = \frac{\kappa_0 \mu_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}}}{\kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}}},\tag{A.8}$$

$$\kappa_n = \kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^\mathsf{T},\tag{A.9}$$

$$\alpha_n = \alpha_0 + \frac{n}{2},\tag{A.10}$$

$$\beta_n = \beta_0 + \frac{1}{2} \left(\boldsymbol{x}_m \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}} + \frac{\kappa_0 \mu_0^2 \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} - 2\kappa_0 \mu_0 \mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}} - \left(\mathbf{1}_n \mathbf{R}_m^{-1} \boldsymbol{x}_m^{\mathsf{T}}\right)^2}{\kappa_0 + \mathbf{1}_n \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}}} \right)$$
(A.11)

646 The normalizing constant is

$$C_n = \frac{\beta_n^{\alpha_n} \kappa_n^{\frac{1}{2}}}{\Gamma(\alpha_n) (2\pi)^{\frac{1}{2}}}.$$
 (A.12)

⁶⁴⁷ Appendix B. The marginal posterior predictive Student's *t*-distribution

In Section 2.5, the Student's *t*-distribution is introduced as the marginal posterior predictive distribution of the RF X(z) for the normal-gamma conjugate prior distribution of the RF parameters. This appendix derives the analytical expressions for the parameters of the marginal posterior predictive distribution as given in Equations (21) to (23).

The marginal posterior predictive PDF at any point $z \in \Omega$ is defined by

$$f(x; \boldsymbol{z} | \mathbf{M}) = \int_{\boldsymbol{\Theta}} f(x; \boldsymbol{z} | \boldsymbol{\theta}, \mathbf{M}) f(\boldsymbol{\theta} | \mathbf{M}) \,\mathrm{d}\boldsymbol{\theta}. \tag{B.1}$$

⁶⁵⁴ $f(\boldsymbol{\theta}|\mathbf{M})$ is the posterior normal-gamma distribution as defined in Equation (9) ⁶⁵⁵ and $f(x; \boldsymbol{z}|\boldsymbol{\theta}, \mathbf{M})$ is a location-specific normal distribution with parameters $\mu_{\boldsymbol{z}}''$ ⁶⁵⁶ and $\lambda_{\boldsymbol{z}}''$ given by Equations (17) and (18). Hence, Equation (B.1) can be ex-⁶⁵⁷ panded as follows:

$$f(x; \boldsymbol{z}|\mathbf{M}) = \int_{\lambda_X=0}^{+\infty} \int_{\mu_X=-\infty}^{+\infty} \mathcal{N}(x|\mu_{\boldsymbol{z}}'', \lambda_{\boldsymbol{z}}'') \mathcal{N}(\mu_X|\mu_n, \kappa_n \lambda_X) \,\mathrm{d}\mu_X \mathcal{G}(\lambda_X|\alpha_n, \beta_n) \,\mathrm{d}\lambda_X$$
(B.2)

⁶⁵⁸ The inner integral involves the convolution of two normal densities:

$$\int_{\mu_X = -\infty}^{+\infty} \mathcal{N}\left(x|\mu_{\boldsymbol{z}}'', \lambda_{\boldsymbol{z}}''\right) \mathcal{N}\left(\mu_X|\mu_n, \kappa_n \lambda_X\right) \mathrm{d}\mu_X = f\left(x; \boldsymbol{z}|\lambda_X, \mathbf{M}\right). \tag{B.3}$$

⁶⁵⁹ For the solution of the integral, the expression for μ_z'' , given in Equation (17) is

⁶⁶⁰ rewritten as follows:

For this special case and noting that λ_{z}'' does not depend on μ_{X} , the marginalization in Equation (B.3) can be solved analytically and results in a normal density $f(x; z | \lambda_{X}, \mathbf{M}) = \mathcal{N}(x | \tilde{\mu}_{z}, \tilde{\lambda}_{z})$, where $\tilde{\mu}_{z}$ and $\tilde{\lambda}_{z}$ are given by the following equations [36]:

$$\tilde{\mu}_{\boldsymbol{z}} = \psi \mu_n + \xi, \qquad (B.5)$$

$$\tilde{\lambda}_{\boldsymbol{z}} = \left(\left(\lambda_{\boldsymbol{z}}^{\prime\prime} \right)^{-1} + \psi^2 \lambda_X^{-1} \kappa_n^{-1} \right)^{-1} = \lambda_X \underbrace{ \left(1 - \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \boldsymbol{R}_{\boldsymbol{z},m}^{\mathsf{T}} + \left(1 - \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} \right)^2 \kappa_n^{-1} \right)^{-1}}_{\tilde{\kappa}_{\boldsymbol{z}}}$$

$$(B.6)$$

⁶⁶⁵ Inserting in Equation (B.2) results in

$$f(x; \boldsymbol{z}|\mathbf{M}) = \frac{\beta_n^{\alpha_n} \left(\tilde{\kappa}_{\boldsymbol{z}}\right)^{\frac{1}{2}}}{\Gamma\left(\alpha_n\right) \left(2\pi\right)^{\frac{1}{2}}} \int_{\lambda_X=0}^{+\infty} \lambda_X^{\alpha_n - \frac{1}{2}} \exp\left(-\lambda_X \left(\beta_n + \frac{\tilde{\kappa}_{\boldsymbol{z}}}{2} \left(x_{\boldsymbol{z}} - \tilde{\mu}_{\boldsymbol{z}}\right)^2\right)\right) d\lambda_X$$
(B.7)

A solution of the integral in Equation (B.7) is readily available and the resulting
expression is as follows [36]:

$$f(x; \boldsymbol{z}|\mathbf{M}) = \frac{\beta_n^{\alpha_n} \left(\tilde{\kappa}_{\boldsymbol{z}}\right)^{\frac{1}{2}}}{\Gamma\left(\alpha_n\right) \left(2\pi\right)^{\frac{1}{2}}} \left(\beta_n + \frac{\tilde{\kappa}_{\boldsymbol{z}}}{2} \left(x_{\boldsymbol{z}} - \tilde{\mu}_{\boldsymbol{z}}\right)^2\right)^{-\frac{1}{2} - \alpha_n} \Gamma\left(\alpha_n + \frac{1}{2}\right). \quad (B.8)$$

To bring $f(x; \mathbf{z} | \mathbf{M})$ into a standardized format, we define $\mu_{\mathbf{z},t} = \tilde{\mu}_{\mathbf{z}}, \lambda_{\mathbf{z},t} = \frac{\tilde{\kappa}_{\mathbf{z}} \alpha_n}{\beta_n}$ and $\nu_t = 2\alpha_n$ [36]. This gives

$$f(x; \boldsymbol{z}|\mathbf{M}) = \frac{\Gamma\left(\frac{\nu_t+1}{2}\right)}{\Gamma\left(\frac{\nu_t}{2}\right)} \left(\frac{\lambda_{\boldsymbol{z},t}}{\pi\nu_t}\right)^{\frac{1}{2}} \left(1 + \frac{\lambda_{\boldsymbol{z},t}}{\nu_t} \left(x_{\boldsymbol{z}} - \mu_{\boldsymbol{z},t}\right)^2\right)^{-\frac{\nu_t}{2} - \frac{1}{2}}.$$
 (B.9)

Equation (B.9) describes the marginal posterior predictive distribution of the RF X(z) given measurement data **M**, which is a Student's *t*-distribution with location parameter $\mu_{z,t}$, scale parameter $\lambda_{z,t}$ and degrees of freedom ν_t defined as follows:

$$\mu_{\boldsymbol{z},t} = \mu_n + \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \left(\boldsymbol{x}_m - \mu_n \mathbf{1}_n \right)^\mathsf{T}, \qquad (B.10)$$

$$\lambda_{\boldsymbol{z},t} = \frac{\alpha_n}{\beta_n \left(1 - \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \boldsymbol{R}_{\boldsymbol{z},m}^{\mathsf{T}} + \left(1 - \boldsymbol{R}_{\boldsymbol{z},m} \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} \right)^2 \kappa_n^{-1} \right)}, \qquad (B.11)$$

$$\nu_t = 2\alpha_n,\tag{B.12}$$

where μ_n , κ_n , α_n and β_n are the posterior parameters of the normal-gamma distribution given by Equations (11) to (14).

⁶⁷⁶ Appendix C. The multivariate posterior predictive Student's *t*-distribution

This section extends the derivation of Appendix B to the multivariate case to derive the parameters for the k-th order posterior predictive Student's tdistribution as given by Equations (23), (29) and (30) in Section 2.6.

The PDF of the posterior predictive distribution of the RF X(z) is

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = \int_{\boldsymbol{\Theta}} f(\boldsymbol{x}; \mathbf{Z} | \boldsymbol{\theta}, \mathbf{M}) f(\boldsymbol{\theta} | \mathbf{M}) \, \mathrm{d}\boldsymbol{\theta}, \qquad (C.1)$$

with $\boldsymbol{x} \in \mathbb{R}^{k}$ and $\mathbf{Z} = [\boldsymbol{z}_{1}, \dots, \boldsymbol{z}_{k}] \in \mathbb{R}^{k \times d}$ denoting any set of spatial points in Ω . $f(\boldsymbol{x}; \mathbf{Z} | \boldsymbol{\theta}, \mathbf{M})$ is a k-variate normal density with mean vector $\boldsymbol{\mu}_{\mathbf{Z}}^{"}$ and precision matrix $\boldsymbol{\Lambda}_{\mathbf{Z}}^{"}$ given by Equations (25) and (26). $f(\boldsymbol{\theta} | \mathbf{M})$ is a normal-gamma distribution as defined in Equation (9) and is independent of the locations \mathbf{Z} . Equation (C.1) is expanded as follows:

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = \int_{\lambda_X = 0}^{+\infty} \int_{\mu_X = -\infty}^{+\infty} \mathcal{N}\left(\boldsymbol{x} | \boldsymbol{\mu}_{\mathbf{Z}}^{"}, \boldsymbol{\Lambda}_{\mathbf{Z}}^{"}\right) \cdot \mathcal{N}\left(\mu_X | \mu_n, \lambda_X \kappa_n\right) \mathrm{d}\mu_X \cdot \mathcal{G}\left(\lambda_X | \alpha_n, \beta_n\right) \mathrm{d}\lambda_X$$
(C.2)

⁶⁸⁶ The inner integral can be solved by rewriting Equation (25) as follows:

$$\boldsymbol{\mu}_{\mathbf{Z}}^{\prime\prime} = \boldsymbol{\mu}_{X} \mathbf{1}_{k} + \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_{m}^{-1} \left(\boldsymbol{x}_{m} - \boldsymbol{\mu}_{X} \mathbf{1}_{n} \right)^{\mathsf{T}} = \boldsymbol{\mu}_{X} \underbrace{ \left(\mathbf{1}_{k} - \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_{m}^{-1} \mathbf{1}_{n}^{\mathsf{T}} \right)}_{\boldsymbol{\psi}} + \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_{m}^{-1} \boldsymbol{x}_{m}^{\mathsf{T}}}_{\boldsymbol{\xi}}.$$

$$(C.3)$$

⁶⁸⁷ Using this expression, the integration over μ_X can be performed analytically ⁶⁸⁸ and results in the density of a multivariate normal distribution $\mathcal{N}\left(\boldsymbol{x}|\tilde{\boldsymbol{\mu}}_{\mathbf{Z}},\tilde{\boldsymbol{\Lambda}}_{\mathbf{Z}}\right)$ ⁶⁸⁹ with parameters given as [36]

$$\tilde{\boldsymbol{\mu}}_{\mathbf{Z}} = \mu_n \boldsymbol{\psi} + \boldsymbol{\xi},\tag{C.4}$$

$$\tilde{\mathbf{\Lambda}}_{\mathbf{Z}} = \left(\left(\mathbf{\Lambda}_{\mathbf{Z}}^{\prime\prime} \right)^{-1} + \boldsymbol{\psi}^{\mathsf{T}} \left(\lambda_{X} \kappa_{n} \right)^{-1} \boldsymbol{\psi} \right)^{-1}.$$
(C.5)

⁶⁹⁰ Substituting Equations (26) and (C.3) into Equation (C.5), $\tilde{\Lambda}_{\mathbf{Z}}$ can be ex-⁶⁹¹ pressed as the following linear function of λ_X :

$$\tilde{\mathbf{\Lambda}}_{\mathbf{Z}} = \lambda_{X} \underbrace{\left(\mathbf{R}_{\mathbf{Z}} - \mathbf{R}_{\mathbf{Z},m}\mathbf{R}_{m}^{-1}\mathbf{R}_{\mathbf{Z},m}^{\mathsf{T}} + \left(\mathbf{1}_{k} - \mathbf{R}_{\mathbf{Z},m}\mathbf{R}_{m}^{-1}\mathbf{1}_{n}^{\mathsf{T}}\right)^{\mathsf{T}}\kappa_{n}^{-1}\left(\mathbf{1}_{k} - \mathbf{R}_{\mathbf{Z},m}\mathbf{R}_{m}^{-1}\mathbf{1}_{n}^{\mathsf{T}}\right)\right)^{-1}}_{\tilde{\mathbf{K}}_{\mathbf{Z}}}$$

$$(C.6)$$

692 Inserting $\mathcal{N}\left(\boldsymbol{x}|\tilde{\boldsymbol{\mu}}_{\mathbf{Z}},\tilde{\boldsymbol{\Lambda}}_{\mathbf{Z}}\right)$ into Equation (C.2) gives

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = \int_{\lambda_X = 0}^{+\infty} \mathcal{N}\left(\boldsymbol{x} | \tilde{\boldsymbol{\mu}}_{\mathbf{Z}}, \tilde{\mathbf{K}}_{\mathbf{Z}} \lambda_X\right) \mathcal{G}\left(\lambda_X | \alpha_n, \beta_n\right) \mathrm{d}\lambda_X.$$
(C.7)

⁶⁹³ Next, an alternative parametrization is introduced, defining $\nu_t = 2\alpha_n$ and $\eta = \frac{\lambda_X \beta_n}{\alpha_n}$. Inserted into Equation (C.7), this gives the following [36]:

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = \int_{\eta=0}^{+\infty} \mathcal{N}\left(\boldsymbol{x} \left| \tilde{\boldsymbol{\mu}}_{\mathbf{Z}}, \tilde{\mathbf{K}}_{\mathbf{Z}} \frac{\eta \alpha_n}{\beta_n} \right. \right) \mathcal{G}\left(\eta \left| \frac{\nu_t}{2}, \frac{\nu_t}{2} \right. \right) \mathrm{d}\eta, \qquad (C.8)$$

⁶⁹⁵ for which a solution is available [36]. The resulting expression is

$$f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = \frac{\Gamma\left(\frac{k+\nu_{t}}{2}\right)}{\Gamma\left(\frac{\nu_{t}}{2}\right)} \left| \tilde{\mathbf{K}}_{\mathbf{Z}} \right|^{\frac{1}{2}} \left(\frac{\alpha_{n}}{\beta_{n} \pi \nu_{t}} \right)^{\frac{k}{2}} \left(1 + \frac{\alpha_{n} \left(\boldsymbol{x} - \tilde{\boldsymbol{\mu}}_{\mathbf{Z}} \right) \tilde{\mathbf{K}}_{\mathbf{Z}} \left(\boldsymbol{x} - \tilde{\boldsymbol{\mu}}_{\mathbf{Z}} \right)^{\mathsf{T}}}{\beta_{n} \nu_{t}} \right)^{-\frac{k+\nu_{t}}{2}}$$
(C.9)

which is a k-variate Student's t-distribution with parameters $\tilde{\boldsymbol{\mu}}_{\mathbf{Z}}$, $\frac{\alpha_n}{\beta_n} \tilde{\mathbf{K}}_{\mathbf{Z}}$ and ν_t . Defining $\boldsymbol{\mu}_{\mathbf{Z},t} = \tilde{\boldsymbol{\mu}}_{\mathbf{Z}}$ and $\boldsymbol{\Lambda}_{\mathbf{Z},t} = \frac{\alpha_n}{\beta_n} \tilde{\mathbf{K}}_{\mathbf{Z}}$ yields the expression of Equation (28) for the k-th order posterior predictive distribution of $X(\boldsymbol{z})$ given measurement data **M**. That is, $f(\boldsymbol{x}; \mathbf{Z} | \mathbf{M}) = f_t(\boldsymbol{x} | \boldsymbol{\mu}_{\mathbf{Z},t}, \boldsymbol{\Lambda}_{\mathbf{Z},t}, \nu_t)$ with parameters given as

$$\boldsymbol{\mu}_{\mathbf{Z},t} = \mu_n \mathbf{1}_k + \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \left(\boldsymbol{x}_m - \mu_n \mathbf{1}_n \right)^\mathsf{T}, \qquad (C.10)$$

$$\mathbf{\Lambda}_{\mathbf{Z},t} = \frac{\alpha_n}{\beta_n} \left(\mathbf{R}_{\mathbf{Z}} - \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \mathbf{R}_{\mathbf{Z},m}^{\mathsf{T}} + \left(\mathbf{1}_k - \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} \right) \kappa_n^{-1} \left(\mathbf{1}_k - \mathbf{R}_{\mathbf{Z},m} \mathbf{R}_m^{-1} \mathbf{1}_n^{\mathsf{T}} \right)^{\mathsf{T}} \right)^{-1}$$
(C.11)

$$\nu_t = 2\alpha_n,\tag{C.12}$$

where μ_n , κ_n , α_n and β_n are the posterior parameters of the normal-gamma distribution given by Equations (11) to (14).

702 Appendix D. The log-Student's *t*-distribution

In Section 2.8, the log-Student's *t*-distribution is introduced as resulting marginal distribution of the posterior predictive RF when the prior RF has lognormal marginal distribution. In this appendix, the log-Student's *t*-distribution and some of its properties are described.

⁷⁰⁷ When X follows a Student's t-distribution, $Y = \exp(X)$ follows the log-⁷⁰⁸ Student's t-distribution [50, 52]. The PDF can be derived as follows:

$$f_{t,\ln}(y) = \left| \frac{\mathrm{dln}(y)}{\mathrm{d}y} \right| f_t(\ln(y)) = \frac{1}{y} f_t(\ln(y)), \qquad (D.1)$$

where $f_t(\cdot)$ is the PDF of the Student's *t*-distribution, which gives

$$f_{t,\ln}(y|\mu_t,\lambda_t,\nu_t) = y^{-1} \frac{\Gamma\left(\frac{\nu_t}{2} + \frac{1}{2}\right)}{\Gamma\left(\frac{\nu_t}{2}\right)} \left(\frac{\lambda_t}{\pi\nu_t}\right)^{\frac{1}{2}} \left(1 + \frac{\lambda_t \left(\ln(y) - \mu_t\right)^2}{\nu_t}\right)^{-\frac{\nu_t}{2} - \frac{1}{2}},$$
(D.2)

where μ_t , λ_t and ν_t are the parameters of the underlying Student's *t*-distribution. The CDF of *Y* is given by the CDF of the underlying Student's *t*-distribution ⁷¹² with argument $\ln(y)$:

$$F_{t,\ln}\left(y|\mu_t,\lambda_t,\nu_t\right) = F_t\left(\ln\left(y\right)|\mu_t,\lambda_t,\nu_t\right). \tag{D.3}$$

The log-Student's *t*-distribution does not have finite moments of any order. A simple proof is given in the following. The expected value of Y is defined as:

$$\mathbf{E}[Y] = \mathbf{E}[\exp(X)], \qquad (D.4)$$

where X follows the Student's t-distribution. The exponential function can be written in terms of the following power series [e.g. 58]:

$$\exp\left(x\right) = \sum_{k=0}^{\infty} \frac{x^k}{k!},\tag{D.5}$$

 $_{717}$ which can be substituted into Equation (D.4) to give:

$$\mathbf{E}[Y] = \mathbf{E}\left[\sum_{k=0}^{\infty} \frac{X^k}{k!}\right] = \sum_{k=0}^{\infty} \frac{\mathbf{E}\left[X^k\right]}{k!}.$$
 (D.6)

⁷¹⁸ $E[X^k]$ is the *k*-th raw moment of the Student's *t*-distributed random variable ⁷¹⁹ X. However, the moments of the Student's *t*-distribution are only finite for ⁷²⁰ orders $k < \nu_t$ [59] and thus, the following holds for E[Y] due to the sum in ⁷²¹ Equation (D.6):

$$\mathbf{E}[Y] \to \infty \text{ for } \nu_t < \infty. \tag{D.7}$$

Since the first-order moment of Y is infinite, all higher-order integer moments of Y, as well as joint moments for the multivariate case, will also be infinite. In the limiting case, when $\nu_t \to \infty$, the log-Student's *t*-distribution converges to the lognormal distribution, which has finite moments of any order.

726 References

⁷²⁷ [1] K.-K. Phoon, F. H. Kulhawy, Characterization of geotechnical variability,

 $_{728}$ Canadian Geotechnical Journal 36 (4) (1999) 612 – 624.

- [2] S. Geyer, I. Papaioannou, C. Kunz, D. Straub, Reliability assessment of
 large hydraulic structures with spatially distributed measurements, Structure and Infrastructure Engineering 16 (2020) 599 612.
- [3] E. Vanmarcke, Random fields: analysis and synthesis, revised and expanded new Edition, World Scientific, 2010.
- [4] M. Grigoriu, Crossings of non-Gaussian translation processes, Journal of
 Engineering Mechanics 110 (4) (1984) 610 620.
- [5] P. Abrahamsen, A review of Gaussian random fields and correlation functions, 2nd Edition, Norwegian Computing Center, 1997.
- [6] Y. Liu, J. Li, S. Sun, B. Yu, Advances in Gaussian random field generation:
 a review, Computational Geosciences (2019) 1 37.
- [7] A. Gelman, J. Carlin, H. Stern, D. Dunson, A. Vehtari, D. Rubin, Bayesian
 data analysis, 3rd Edition, Chapman & Hall/CRC texts in statistical science, CRC, Boca Raton, FL, 2013.
- [8] S. Brooks, A. Gelman, G. Jones, X.-L. Meng, Handbook of Markov chain
 Monte Carlo, Chapman & Hall/CRC handbooks of modern statistical
 methods, CRC, Boca Raton, FL, 2011.
- [9] P. Del Moral, A. Doucet, A. Jasra, Sequential Monte Carlo samplers, Journal of the Royal Statistical Society: Series B (Statistical Methodology)
 68 (3) (2006) 411 436.
- [10] J. Ching, Y.-C. Chen, Transitional Markov chain Monte Carlo method
 for Bayesian model updating, model class selection, and model averaging,
 Journal of Engineering Mechanics 133 (7) (2007) 816 832.
- [11] D. Straub, I. Papaioannou, Bayesian updating with structural reliability
 methods, Journal of Engineering Mechanics 141 (3) (2015) 04014134.

- ⁷⁵⁴ [12] W. Betz, I. Papaioannou, J. L. Beck, D. Straub, Bayesian inference with
 ⁷⁵⁵ subset simulation: strategies and improvements, Computer Methods in
 ⁷⁵⁶ Applied Mechanics and Engineering 331 (2018) 72 93.
- ⁷⁵⁷ [13] F. Uribe, I. Papaioannou, W. Betz, D. Straub, Bayesian inference of ran⁷⁵⁸ dom fields represented with the Karhunen–Loève expansion, Computer
 ⁷⁵⁹ Methods in Applied Mechanics and Engineering 358 (2020) 112632.
- [14] I. Papaioannou, D. Straub, Learning soil parameters and updating geotech nical reliability estimates under spatial variability theory and application
 to shallow foundations, Georisk: Assessment and Management of Risk for
 Engineered Systems and Geohazards 11 (1) (2017) 116 128.
- [15] M. Stein, Interpolation of spatial data: some theory for kriging, Springer
 series in statistics, Springer, New York City, NY, 1999.
- [16] M. S. Handcock, M. L. Stein, A Bayesian analysis of kriging, Technometrics
 35 (4) (1993) 403 410.
- [17] S. Banerjee, B. P. Carlin, A. E. Gelfand, Hierarchical modeling and analysis for spatial data, 2nd Edition, Chapman & Hall/CRC monographs on
 statistics & applied probability, CRC, Boca Raton, FL, 2014.
- [18] C. Rasmussen, C. Williams, Gaussian processes for machine learning,
 Adaptive computation and machine learning, MIT, Cambridge, MA, 2006.
- [19] O. Ditlevsen, N. J. Tarp-Johansen, H. Denver, Bayesian soil assessments
 combining prior with posterior censored samples, Computers and Geotechnics 26 (3-4) (2000) 187–198.
- [20] J. Ching, J.-S. Wang, Application of the transitional Markov chain Monte
 Carlo algorithm to probabilistic site characterization, Engineering Geology
 203 (2016) 151 167.
- Y. Wang, Z. Cao, D. Li, Bayesian perspective on geotechnical variability
 and site characterization, Engineering Geology 203 (2016) 117 125.

- [22] S.-H. Jiang, I. Papaioannou, D. Straub, Bayesian updating of slope reli ability in spatially variable soils with in-situ measurements, Engineering
 Geology 239 (2018) 310 320.
- [23] J. Ching, K.-K. Phoon, Characterizing uncertain site-specific trend function by sparse Bayesian learning, Journal of Engineering Mechanics 143 (7)
 (2017) 04017028.
- [24] J. Ching, W.-H. Huang, K.-K. Phoon, 3D probabilistic site characterization
 by sparse Bayesian learning, Journal of Engineering Mechanics 146 (12)
 (2020) 04020134.
- [25] J. Ching, Z. Yang, K.-K. Phoon, Dealing with nonlattice data in three dimensional probabilistic site characterization, Journal of Engineering Me chanics 147 (5) (2021) 06021003.
- [26] Y. Wang, T. Zhao, Statistical interpretation of soil property profiles from
 sparse data using Bayesian compressive sampling, Géotechnique 67 (6)
 (2017) 523 536.
- [27] Y. Wang, T. Zhao, K.-K. Phoon, Direct simulation of random field samples
 from sparsely measured geotechnical data with consideration of uncertainty
 in interpretation, Canadian Geotechnical Journal 55 (6) (2018) 862 880.
- [28] Y. Wang, T. Zhao, Y. Hu, K.-K. Phoon, Simulation of random fields with
 trend from sparse measurements without detrending, Journal of Engineering Mechanics 145 (2) (2019) 04018130.
- [29] S. Montoya-Noguera, T. Zhao, Y. Hu, Y. Wang, K.-K. Phoon, Simulation of
 non-stationary non-Gaussian random fields from sparse measurements using Bayesian compressive sampling and Karhunen–Loève expansion, Structural Safety 79 (2019) 66 79.
- [30] Y. Hu, T. Zhao, Y. Wang, C. Choi, C. W. W. Ng, Direct simulation of two dimensional isotropic or anisotropic random field from sparse measurement

- using Bayesian compressive sampling, Stochastic Environmental Research
 and Risk Assessment 33 (8) (2019) 1477 1496.
- [31] T. Zhao, Y. Wang, Simulation of cross-correlated random field samples
 from sparse measurements using bayesian compressive sensing, Mechanical
 Systems and Signal Processing 112 (2018) 384 400.
- [32] J. Benjamin, C. Cornell, Probability, statistics, and decision for civil engineers, Dover books on engineering, McGraw-Hill, New York City, NY,
 1970.
- [33] R. Rackwitz, Predictive distribution of strength under control, Matériaux
 et Constructions 16 (1983) 259 267.
- [34] European Committee for Standardization, EN 1990:2002-04: Eurocode 0:
 Basis of structural desgin, European standard, European Committee for
 Standardization (2002).
- [35] G. Box, G. Tiao, Bayesian inference in statistical analysis, revised new
 Edition, Wiley Classics Library, John Wiley & Sons, 2011.
- [36] C. M. Bishop, Pattern recognition and machine learning, Information science and statistics, Springer, New York City, NY, 2006.
- ⁸²⁵ [37] E. H. Vanmarcke, Probabilistic modeling of soil profiles, Journal of the Geotechnical Engineering Division 103 (11) (1977) 1227 – 1246.
- [38] K.-K. Phoon, S.-T. Quek, P. An, Identification of statistically homogeneous
 soil layers using modified Bartlett statistics, Journal of Geotechnical and
 Geoenvironmental Engineering 129 (7) (2003) 649 659.
- [39] F. V. Jensen, T. D. Nielsen, Bayesian networks and decision graphs, 2nd
 Edition, Information science and statistics, Springer, New York City, NY,
 2007.

- [40] H. Raiffa, R. Schlaifer, Applied statistical decision theory, Studies in man-
- agerial economics, Division of research, graduate school of business admin istration, Harvard University, Cambridge, MA, 1961.
- ⁸³⁶ [41] B. Matérn, Spatial variation, 2nd Edition, Lecture notes in statistics,
 ⁸³⁷ Springer, New York City, NY, 1986.
- [42] M. DeGroot, Optimal Statistical Decisions, McGraw-Hill series in proba bility and statistics, McGraw-Hill, New York City, NY, 1969.
- [43] S. Kotz, S. Nadarajah, Multivariate t-distributions and their applications,
 Cambridge University, 2004.
- ⁸⁴² [44] S. Banerjee, Modeling massive spatial datasets using a conjugate Bayesian
 ⁸⁴³ linear modeling framework, Spatial Statistics 37 (2020) 100417.
- ⁸⁴⁴ [45] R. G. Ghanem, P. D. Spanos, Stochastic finite elements. A spectral approach, revised Edition, Dover civil and mechanical engineering, Dover,
 ⁸⁴⁶ 2012.
- ⁸⁴⁷ [46] K. P. Murphy, Machine learning: a probabilistic perspective, Adaptive
 ⁸⁴⁸ computation and machine learning, MIT, Cambridge, MA, 2013.
- [47] D. Savvas, I. Papaioannou, G. Stefanou, Bayesian identification and model
 comparison for random property fields derived from material microstructure, Computer Methods in Applied Mechanics and Engineering 365 (2020)
 113026.
- [48] C. Li, A. D. Kiureghian, Optimal discretization of random fields, Journal
 of Engineering Mechanics 119 (6) (1993) 1136 1154.
- [49] P.-L. Liu, A. D. Kiureghian, Multivariate distribution models with prescribed marginals and covariances, Probabilistic Engineering Mechanics
 1 (2) (1986) 105 112.

- ⁸⁵⁸ [50] D. T. Cassidy, M. J. Hamp, R. Ouyed, Pricing European options with
 ⁸⁵⁹ a log Student's t-distribution: a Gosset formula, Physica A: Statistical
 ⁸⁶⁰ Mechanics and its Applications 389 (24) (2010) 5736 5748.
- ⁸⁶¹ [51] D. T. Cassidy, M. J. Hamp, R. Ouyed, Log Student's t-distribution-based
 option sensitivities: Greeks for the Gosset formulae, Quantitative Finance
 ⁸⁶³ 13 (8) (2013) 1289 1302.
- ⁸⁶⁴ [52] L. H. Vanegas, G. A. Paula, Log-symmetric distributions: statistical prop⁸⁶⁵ erties and parameter estimation, Brazilian Journal of Probability and
 ⁸⁶⁶ Statistics 30 (2) (2016) 196 220.
- [53] P. W. Mayne, CPT Soundings ANSS Seismic at sta-867 Oct-Nov 2002. June-September tions. 2003,geosys-868 tems.ce.gatech.edu/Faculty/Mayne/Research/sound2003/anssall/index.htm 869 (accessed Mar 09, 2020) (2003). 870
- ⁸⁷¹ [54] C. P. Robert, The Bayesian choice: from decision-theoretic foundations to
 ⁸⁷² computational implementation, 2nd Edition, Springer texts in statistics,
 ⁸⁷³ Springer, 2007.
- [55] A. Westendarp, H. Becker, J. Bödefeld, H. Fleischer, C. Kunz, M. Maisner,
 H. Müller, A. Rahimi, T. Reschke, F. Spörel, Erhaltung und Instandsetzung von massiven Verkehrswasserbauwerken [Maintenance and repair of
 massive hydraulic structures], Beton-Kalender 2015, John Wiley & Sons,
 2015, Ch. IV, pp. 185 246.
- ⁸⁷⁹ [56] H. Zhu, L. Zhang, Characterizing geotechnical anisotropic spatial variations
 ⁸⁸⁰ using random field theory, Canadian Geotechnical Journal 50 (7) (2013) 723
 ⁸⁸¹ 734.
- ⁸⁸² [57] X. Nie, J. Zhang, H. Huang, Z. Liu, S. Lacasse, Scale of fluctuation for
 ⁸⁸³ geotechnical probabilistic analysis, in: Geotechnical Safety and Risk V,
 ⁸⁸⁴ IOS, 2015, pp. 834 840.

- [58] W. Rudin, Real and Complex Analysis, 3rd Edition, higher mathematics
 series, McGraw-Hill, New York City, NY, 1987.
- [59] G. Casella, R. Berger, Statistical inference, 2nd Edition, Duxbury advanced
- series in statistics and decision sciences, Thomson Learning, Pacific Grove,
- ⁸⁸⁹ CA, 2002.